

Journal

The TapeTrack Journal is a database containing operational activity recorded by the TapeTrack Framework Server.

Journal entries provide the source data used to create Customer statistics (`.ttstats`) files for billing.

The Journal records activity occurring within TapeTrack, including Volume storage and movement events. [TMSS10LogStatsExtractDB](#) reads the Journal and creates a separate statistics extract for each Customer within the selected date range.

The Journal does not contain the Customer's billing rates or final invoice items. Rates, package assignments and billing calculations are applied later by [TMSS10LogStatsProcess](#).

Purpose

The Journal provides an authoritative record of TapeTrack activity that may be used for reporting, statistics and billing.

The Journal can be used to:

- Record operational activity generated by the TapeTrack Framework Server.
- Provide the source records for Customer billing statistics.
- Retain activity for a defined period.
- Support the extraction of Customer-specific `.ttstats` files.
- Provide an audit trail between TapeTrack activity and invoice quantities.
- Allow billing statistics to be regenerated from source activity.
- Support investigation of missing or unexpected billing quantities.

The billing relationship is:

TapeTrack Framework Server → Journal → TMSS10LogStatsExtractDB → Customer-ID.`ttstats`

Journal Activity

The TapeTrack Framework Server writes activity to the Journal as TapeTrack operations occur.

Depending on the installed version and configuration, Journal activity may include:

- Volume movements.
- Storage activity.
- Repository activity.
- Deliveries and collections.
- Customer activity.
- Media activity.
- Other operational statistics required for reporting or billing.

The exact billing result depends on:

- The activity stored in the Journal.
- The Customer associated with the activity.
- The selected extraction date range.
- The statistics created by `TMSS10LogStatsExtractDB`.
- The Package Map and Billing Rules used during processing.

The presence of an activity in the Journal does not necessarily mean that it will be billed. The Billing Rules determine which extracted statistics are converted into invoice items.

Journal Database Location

The Journal database is maintained by the TapeTrack Framework Server.

Its physical location depends on:

- The TapeTrack Framework Server installation directory.
- The operating system.
- The installed TapeTrack version.
- The Framework Server configuration.

The Journal database should be accessed using the TapeTrack server utilities rather than edited directly.



Do not manually modify, replace or delete Journal database files while the TapeTrack Framework Server is operating. Direct changes may damage the Journal or prevent billing statistics from being reproduced.

The account running the Journal extraction must have sufficient permission to:

- Access the TapeTrack Framework Server installation.
- Read the Journal database.
- Execute `TMSS10LogStatsExtractDB`.
- Write the generated `.ttstats` files to the billing extract directory.

Journal Extraction

`TMSS10LogStatsExtractDB` creates an extract file for each Customer from the Journal database.

The extraction should specify the required billing date range.

For example, an extraction containing activity for three Customers may create:

Customer-ID	Extract File
US01	US01.ttstats
US02	US02.ttstats
US03	US03.ttstats

Each .ttstats file contains the statistics extracted for its Customer.

The resulting files are processed using [TMSS10LogStatsProcess](#).

Date Range

The extraction date range determines which Journal records are included in the Customer statistics files.

The date range must:

- Match the approved billing period.
- Begin immediately after the previous billing period.
- Avoid overlapping a previously invoiced period.
- Avoid leaving gaps between billing periods.
- Use the correct server date and time zone.

Example monthly billing periods:

Billing Period	Start Date	End Date
January 2026	2026-01-01	2026-01-31
February 2026	2026-02-01	2026-02-28
March 2026	2026-03-01	2026-03-31



The precise handling of start times, end times and inclusive boundaries must be confirmed for the installed version of TMSS10LogStatsExtractDB. An overlapping boundary may cause activity to be billed twice.

Relationship to Billing Files

The Journal is the first data stage in the TapeTrack billing process.

File or Component	Purpose
TapeTrack Framework Server	Records operational activity.
Journal	Stores the source activity records.
TMSS10LogStatsExtractDB	Extracts Journal statistics for each Customer.
Customer-ID.ttstats	Contains the extracted Customer activity and quantities.
Customer Description Map	Maps the Customer-ID to a readable description.
Package Map	Selects the Customer's billing package.

File or Component	Purpose
Billing Rules	Converts statistics into invoice items and charges.
TMSS10LogStatsProcess	Applies the maps and Billing Rules and produces billing XML.
tapetrack.xslt	Controls how the billing XML is displayed.
XMLQuickBooks Mapping	Maps approved billing XML to QuickBooks customers and items.

The complete process is:

TapeTrack → Journal → Extract → TTSTATS → Process → Billing XML → QuickBooks Invoice

Viewing Journal Information

TMSS10LogStatsPrintDB can be used to print the contents of the Journal database.

This utility is useful when:

- Confirming that activity exists for a Customer.
- Investigating missing .ttstats records.
- Comparing Journal activity with billing quantities.
- Checking activity within a date range.
- Troubleshooting unexpected invoice items.

TMSS10LogStatsPrintDB displays Journal information. It does not create Customer billing XML or QuickBooks invoices.

Validation

The Journal and extraction should be validated before production billing is processed.

Check that:

- The correct Journal database is being used.
- The Framework Server recorded activity during the billing period.
- The extraction date range is correct.
- The server date, time and time zone are correct.
- A .ttstats file was generated for each expected Customer.
- The generated files are not unexpectedly empty.
- The extraction process completed without errors.
- The Journal was backed up before any administrative maintenance.
- The extracted quantities are reasonable for the billing period.

A billing control record should include:

Control	Example
Framework Server	Production TapeTrack Server
Billing period	2026-07-01 to 2026-07-31

Control	Example
Extraction utility	TMSS10LogStatsExtractDB
Extraction date	2026-08-01
Output directory	C:\TapeTrack\Billing\2026-07\Input
Customer files created	US01.ttstats, US02.ttstats
Extraction status	Completed
Reviewer	Authorized billing administrator

Troubleshooting

No TTSTATS Files Are Created

Check that:

- TMSS10LogStatsExtractDB completed successfully.
- The correct Journal database was selected.
- Journal records exist within the selected date range.
- The output directory exists.
- The extraction account can read the Journal.
- The extraction account can write to the output directory.
- The date range was entered in the expected format.

Customer TTSTATS File Is Missing

Confirm that:

- The Customer exists in TapeTrack.
- The Customer had Journal activity during the billing period.
- The Customer-ID is correct.
- The extraction covered the complete billing period.
- The file was not moved, renamed or archived.
- The extraction log does not contain an error for the Customer.

A missing Customer file may be valid if the Customer had no relevant Journal activity. This should be confirmed before excluding the Customer from billing.

TTSTATS File Is Empty

Check that:

- Journal activity exists for the Customer.
- The selected date range includes the activity.
- The correct production Journal was processed.
- The server date and time zone are correct.
- The Customer activity is of a type included in the statistics extraction.

Billing Activity Is Missing

Compare:

1. The operational event in TapeTrack.
2. The corresponding Journal entry.
3. The generated `.ttstats` file.
4. The Billing Rules applied by `TMSS10LogStatsProcess`.
5. The resulting billing XML.

This identifies the stage at which the activity was excluded.

Activity Location	Likely Issue
Missing from TapeTrack	Operational event was not recorded.
Present in TapeTrack but missing from Journal	Framework Server or Journal recording issue.
Present in Journal but missing from TTSTATS	Extraction date range or extraction issue.
Present in TTSTATS but missing from billing XML	Package Map or Billing Rules issue.
Present in billing XML but missing from QuickBooks	XMLQuickBooks mapping or import issue.

Billing Activity Is Duplicated

Check that:

- Extraction date ranges do not overlap.
- The same `.ttstats` file was not processed twice.
- The same billing XML was not submitted twice.
- Duplicate Billing Rules are not matching the same statistic.
- Previously processed files were moved to an archive directory.

Journal Cannot Be Read

Confirm that:

- The correct server utility is being used.
- The Journal database exists.
- The utility account has the required permissions.
- The database is not damaged.
- The installed utility version is compatible with the Framework Server.
- No unsupported direct changes were made to the Journal files.

If the Journal appears damaged or unreadable, contact TapeTrack Support before attempting repairs.

Backup and Retention

The Journal supports operational history and billing reconstruction and should be included in the Framework Server backup process.

The backup and retention policy should consider:

- Customer contract requirements.
- Accounting record-retention requirements.
- The ability to reproduce billing statistics.
- Audit and dispute periods.
- Available storage.
- TapeTrack Support recommendations.
- Applicable legal and regulatory requirements.

Retain the following billing records together where possible:

- Billing period details.
- Journal backup or reference.
- Customer .ttstats files.
- Customer Description Map.
- Package Map.
- Billing Rules.
- Stylesheet.
- Billing XML.
- QuickBooks invoice number.
- Processing and approval logs.

Recommended Practices

- Treat the Journal as an authoritative operational record.
- Do not manually edit the Journal database.
- Back up the Journal as part of the Framework Server backup.
- Use non-overlapping billing extraction periods.
- Record the exact extraction date range.
- Review extraction logs before processing billing.
- Investigate missing or empty Customer files.
- Retain the extracted TTSTATS files with the billing output.
- Restrict database access to authorized administrators.
- Contact TapeTrack Support before attempting Journal repair.

Security

The Journal may contain Customer, Volume, Repository and operational activity information.

Access should therefore be restricted to:

- TapeTrack Framework Server services.
- TapeTrack administrators.
- Authorized billing staff requiring access.
- The account running TMSS10LogStatsExtractDB.
- The account running authorized backup processes.

The Journal should not be publicly accessible or stored in an unsecured shared directory.

See Also

- [TMSS10LogStatsProcess](#)
- [Customer-ID](#)
- [Customer TTSTATS File](#)
- [Customer Description Map](#)
- [Package Map](#)
- [Billing Rules](#)
- [TapeTrack XML Stylesheet](#)
- [Billing Process](#)
- [Billing XML](#)
- [XMLQuickBooks Mapping](#)

[billing](#), [journal](#), [database](#), [statistics](#), [ttstats](#), [framework server](#), [quickbooks](#)

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/billing/journal?rev=1787023554>

Last update: **2026/08/18 03:25**

