

Journal

The TapeTrack Journal is a database containing operational activity recorded by the TapeTrack Framework Server.

Journal entries provide the source data used to create Customer statistics (`.ttstats`) files for billing.

The Journal records activity occurring within TapeTrack, including Volume storage and movement events. [TMSS10LogStatsExtractDB](#) reads the Journal and creates a separate statistics extract for each Customer within the selected date range.

The Journal does not contain the Customer's billing rates or final invoice items. Rates, package assignments and billing calculations are applied later by [TMSS10LogStatsProcess](#).

Purpose

The Journal provides an authoritative record of TapeTrack activity that may be used for reporting, statistics and billing. The Journal can be used to:

- Record operational activity generated by the TapeTrack Framework Server.
- Filter activity for a defined period.
- Support the extraction of Customer-specific `.ttstats` files.
- Provide an audit trail between TapeTrack activity and invoice quantities.

Journal Activity

The TapeTrack Framework Server writes activity to the Journal as TapeTrack operations occur.

Depending on the installed version and configuration, Journal activity may include Volume movements, storage activity, repository activity, media activity, other operational statistics required for reporting or billing.

The exact billing result depends on:

- The activity stored in the Journal.
- The Customer associated with the activity.
- The selected extraction date range.
- The statistics created by [TMSS10LogStatsExtractDB](#).
- The Package Map and Billing Rules used during processing.

Journal Database Location

The Journal database is maintained by the TapeTrack Framework Server.

Its physical location depends on:

- The TapeTrack Framework Server installation directory.
- The operating system.
- The installed TapeTrack version.
- The Framework Server configuration.

The Journal database should be accessed using the TapeTrack server utilities rather than edited directly.



Do not manually modify, replace or delete Journal database files while the TapeTrack Framework Server is operating. Direct changes may damage the Journal or prevent billing statistics from being reproduced.

The account running the Journal extraction must have sufficient permission to:

- Access the TapeTrack Framework Server installation.
- Read the Journal database.
- Execute `TMSS10LogStatsExtractDB`.
- Write the generated `.ttstats` files to the billing extract directory.

Viewing Journal Information

[TMSS10LogStatsPrintDB](#) can be used to print the contents of the Journal database.

This utility is useful when:

- Confirming that activity exists for a Customer.
- Investigating missing `.ttstats` records.
- Comparing Journal activity with billing quantities.
- Checking activity within a date range.
- Troubleshooting unexpected invoice items.

[TMSS10LogStatsPrintDB](#) displays Journal information. It does not create Customer billing XML or QuickBooks invoices.

Troubleshooting

Journal Cannot Be Read

Confirm that:

- The correct server utility is being used.
- The Journal database exists.
- The utility account has the required permissions.
- The database is not damaged.

- The installed utility version is compatible with the Framework Server.
- No unsupported direct changes were made to the Journal files.

If the Journal appears damaged or unreadable, contact TapeTrack Support before attempting repairs.

Backup and Retention

The Journal supports operational history and billing reconstruction and should be included in the Framework Server backup process.

The backup and retention policy should consider:

- Customer contract requirements.
- Accounting record-retention requirements.
- The ability to reproduce billing statistics.
- Audit and dispute periods.
- Available storage.
- TapeTrack Support recommendations.
- Applicable legal and regulatory requirements.

Retain the following billing records together where possible:

- Billing period details.
- Journal backup or reference.
- Customer .ttstats files.
- Customer Description Map.
- Package Map.
- Billing Rules.
- Stylesheet.
- Billing XML.
- QuickBooks invoice number.
- Processing and approval logs.

Recommended Practices

- Treat the Journal as an authoritative operational record.
- Do not manually edit the Journal database.
- Back up the Journal as part of the Framework Server backup.
- Use non-overlapping billing extraction periods.
- Record the exact extraction date range.
- Review extraction logs before processing billing.
- Investigate missing or empty Customer files.
- Retain the extracted TTSTATS files with the billing output.
- Restrict database access to authorized administrators.
- Contact TapeTrack Support before attempting Journal repair.

Security

The Journal may contain Customer, Volume, Repository and operational activity information.

Access should therefore be restricted to:

- TapeTrack Framework Server services.
- TapeTrack administrators.
- Authorized billing staff requiring access.
- The account running TMSS10LogStatsExtractDB.
- The account running authorized backup processes.

The Journal should not be publicly accessible or stored in an unsecured shared directory.

See Also

- [TMSS10LogStatsProcess](#)
- [Customer-ID](#)
- [Customer TTSTATS File](#)
- [Customer Description Map](#)
- [Package Map](#)
- [Billing Rules](#)
- [TapeTrack XML Stylesheet](#)
- [Billing Process](#)
- [Billing XML](#)
- [XMLQuickBooks Mapping](#)

[billing](#), [journal](#), [database](#), [statistics](#), [ttstats](#), [framework server](#), [quickbooks](#)

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/billing/journal?rev=1787024354>

Last update: **2026/08/18 03:39**

