

Command Line Server Argument

The logonstring argument sets the Server logon information in the format user:password@server:port.

In the event that this argument is not passed the default will be batch:batch@localhost:5000.

Password interpretation

When specifying the password value, the following rules will apply to the interpretation of this value:

- By default the password value will be treated as the path to a file which contains a single record representing the password, rather than the password itself.
- If you wish the password value to be the literal password (rather than a file) the password should be prepended with a dash (jsmith:-mypassword@server).
- You can also have the program read the password as the first record of stdin by prepending the password with a plus symbol (jsmith:+@server).

In the event that the password is all upper case and 32 characters in length, the password will be considered an MD5 hash of the password and passed to the server without subsequent MD5 hashing.

Environmental Variables

- TMSSPWPATH
- TMSSKERBEROS
- TMSSNOMD5
- TMSSERVERPROXY
- TMSSUSERINHERIT

Examples

Connect to localhost with User-ID batch, password in file c:\tapetrack\pw\batch on port **5000**.

```
-S localhost
```

Connect to tapetrack.gazillabyte.com with User-ID jsmith and prompt for the password on port **443**.

```
-S jsmith:+@tapetrack.gazillabyte.com:443
```

Connect to tapetrack.gazillabyte.com with User-ID jsmith and password of mypassword on port **443**.

-S jsmith:-mypassword@tapetrack.gazillabyte.com:443

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**



Permanent link:
https://rtfm.tapetrack.com/cli/server_argument

Last update: **2025/01/21 22:07**