

Command Line Server Argument

The `logonstring` argument sets the Server logon information in the format `user:password@server:port`.

In the event that this argument is not passed the default will be `batch:batch@localhost:5000`.

- By default the password value will be treated as the path to a file which contains a single record

representing the password, rather than the password itself.

- If you wish the password value to be the literal password (rather than a file) the password should be

prepended with a dash (`jsmith:-mypassword@server`).

- You can also have the program read the password as the first record of `stdin` by prepending the

password with a plus symbol (`jsmith:+@server`).

In the event that the password is all upper case and 32 characters in length, the password will be considered an MD5 hash of the password and passed to the server without subsequent MD5 hashing.

Environmental Variables

- [TMSSPPATH](#)

Examples

Connect to `localhost` with User-ID `batch`, password in file `c:\tapetrack\pw\batch` on port **5000**.

```
-S localhost
```

Connect to `tapetrack.gazillabyte.com` with User-ID `jsmith` and prompt for the password on port **443**.

```
-S jsmith:+@tapetrack.gazillabyte.com:443
```

Connect to `tapetrack.gazillabyte.com` with User-ID `jsmith` and password of `mypassword` on port

443.

```
-S jsmith:-mypassword@tapetrack.gazillabyte.com:443
```

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

https://rtfm.tapetrack.com/cli/server_argument?rev=1553707677

Last update: **2025/01/21 22:07**

