TapeTrack Sync Fields

Field	Max	Description
CUSTOMER	4	Customer-ID
MEDIA	4	Media-ID
VOLUME	10	Volume-ID
REPOSITORY	4	Repository-ID
REPOSITORY_DESC	20	Description of Repository (will be used to set the REPOSITORY field)
SLOT	10	Slot for Repository.
DATACLUSTER	256	Data Cluster Value (Data Cluster must already exist)
DESCRIPTION	256	Volume Description (use program flag to set Extended Attributes)
MOVEDATE	64	Move Date (must have SetMoveDateFormat defined)
WRITETIME	64	Write Time (must have SetWriteTimeFormat defined)
CONTAINER	20	Fully qualified Container barcode
SYSTEM	10	System this Volume belongs to
ENCRYPTED	10	Is Volume encrypted (YES, NO, TRUE, FALSE)
SCRATCH	10	Is Volume scratch (YES, NO, TRUE, FALSE)

Addition Sync Fields

Addition Sync fields that can be used to extract data into for comparison when using Translation statements. These are not fields that can be set directly in TapeTrack.

User1
User2
User3
User4
User5
User6
User7
User8
User9

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/cli/sync_fields?rev=1560993659

Last update: 2025/01/21 22:07

