

# TMSS10BatchLoader

## Synopsis

```
TMSS10BatchLeader [-c configuration file] [-S logonstring]
```

## Description

Creates Customer, Media and Repositories by loading a configuration file into the TapeTrack Database.

## Options

- -c The config file argument specifies the path to the Batch Configuration File.
- -S Logon string argument sets the [Server logon information](#).

## Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

## Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

## Environment

## Files

## Example

### Configuration File

Configuration file to load to create two Customers with attributes

Customer 0001

- Customer ID: 0001, Customer Description: ACME Computers
- Media ID: LTO, Media Description: LTO Cartridge
- Repository ID: LIBR, Repository Description: Library, Repository Type: 1, Next Repository: OFFS
- Repository ID: OFFS, Repository Description: Iron Mountain, Repository Type: 2
- Repository ID: DEST, Repository Description: Destroyed, Repository Type: 6
- Repository ID: HOLD, Repository Description: Legal Hold, Repository Type: 4

#### Customer 0002

- Customer ID: 0002, Customer Description: Bond Corporation
- Media ID: 3490, Media Description: IBM 3490 Cartridge.
- Repository ID: LIBR, Repository Description: Library, Repository Type: 1, Next Repository: OFFS
- Repository ID: OFFS, Repository Description: Iron Mountain, Repository Type: 2 and Next Repository: LIBR.

```
setup=
{
  customers=
  (
    {
      id="0001"; description="ACME Computers";

      media=
      (
        {
          id="LTO"; description="LTO Cartridge";

          repositories=
          (
            { id="LIBR"; description="Library"; type=3;
next="OFFS"; },
            { id="OFFS"; description="Iron Mountain"; type=2;
next="LIBR"; },
            { id="DEST"; description="Destroyed"; type=6; },
            { id="HOLD"; description="Legal hold"; type=4; }
          )
        },
        {
          id="3490"; description="IBM 3490 Cartridge";

          repositories=
          (
            { id="LIBR"; description="Library"; type=1;
next="OFFS"; },
            { id="OFFS"; description="Iron Mountain"; type=2;
next="LIBR"; }
          )
        }
      )
    },
  ),
},
```

```
{
  id="0002"; description="Bond Corporation";
  media=
  (
    {
      id="LT0"; description="LT0 Cartridge";

      repositories=
      (
        { id="LIBR"; description="Library"; type=1; },
        { id="OFFS"; description="Iron Mountain"; type=2; }
      )
    },
    {
      id="3490"; description="IBM 3490 Cartridge";

      repositories=
      (
        { id="LIBR"; description="Library"; type=1; },
        { id="OFFS"; description="Iron Mountain"; type=2; }
      )
    }
  )
};
```

## Command line syntax

```
TMSS10BatchLoader -S user:-password@localhost -c master.cfg
```

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/cli/tmss10batchloader?rev=1551054820>

Last update: **2025/01/21 22:07**

