

TMSS10ExportFile

TMSS10ExportFile will extract TapeTrack data so that it can be reloaded to another TapeTrack Server.

Synopsis

```
TMSS10ExportFile [-S logon string] [-V volume filter] [-c config file] [-f output file] [-h download history]
```

Options

- -S The Logon string argument sets the [Server Logon Information](#)
- -V [Volume Filter](#) which can be used to filter the traversal of [Customer](#), [Media](#), [Volume](#), [Repository](#) and [Flag](#) values.
- -c The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of [Customer](#), [Media](#) and [Volumes](#), perform advanced Barcode pre and post processing and route program output to syslogd. Configuration File capabilities vary from program to program but the syntax remains the same. In the event that logic is not supported it will simply be ignored.
- -f Output file name.
- -h Don't download [Volume](#) history records (default = false).

If an argument value starts with the value **FI:**, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME_volumes has the content **ACME_*** *****, specifying **FI:/etc/ACME_volumes** will have the same effect as **-V ACME.*.***. Using **FI:** to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with ***LIST:** then rather than matching the literal value, each record in the file specified as ***LIST:filename** will be tested. If one matches the match will succeed.

2021/06/16 02:14 · Scott Cunliffe
[include page](#)

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff.

If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

Exit Statuses

1. **zero** Program has ended successfully.

2. **non-zero** Program has not ended successfully.

Files

stdout: Output Reports.

stderr: Diagnostic messages.

stdin: Program input.

Example

Command line syntax

```
TMSS10ExportFile -S user:-password@server -V "US03.*.*" -f  
"TapeTrackExport_November.TTEXPORT" -h
```

Output

Outputs a file named TapeTrackExport_November.TTEXPORT of **Customer** US03 without **Volume** history for use in importing data into another TapeTrack server.

See Also

[Command Line Utility Troubleshooting and Diagnosis](#)

[Changelog](#)

Cannot load rss feed.

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**



Permanent link:

<https://rtfm.tapetrack.com/cli/tmss10exportfile>

Last update: **2025/07/04 04:45**