

TMSS10LogStatsProcess

TMSS10LogStatsProcess processes a TapeTrack Statistics file, apply calculations and produce a report in XML format.

Synopsis

```
TMSS10LogStatsProcess [-M customer map file] [-N no xml preamble] [-P package map] [-X xml stylesheet] [-c config file] [-i input ttstats file] [-l list stats definition language syntax]
```

If an argument value starts with the value `FI:`, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named `ACME_volumes` has the content `ACME_*.*`, specifying `FI:/etc/ACME_volumes` will have the same effect as `-V ACME_*.*`. Using `FI:` to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with `*LIST:` then rather than matching the literal value, each record in the file specified as `*LIST:filename` will be tested. If one matches the match will succeed.

2021/06/16 02:14 · Scott Cunliffe

[include page](#)

Options

- `-M` Customer Description Map File
- `-N` No XML preamble (default = false)
- `-P` Package Map File
- `-X` XML Style Sheet (default = `tapetrack.xslt`)
- `-c` Config File (default = `default.ttsdef`)
- `-i` Input TTSTATS file
- `-l` List Stats Definition Language syntax (default = false)

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff.

If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

Example

Command line syntax

```
TMSS10LogStatsProcess -i 0001.ttstats -M customer.txt -P package.txt > Billing_0002.xml
```

Output

```
<?xml version="1.0" encoding="ISO8859-1" ?>
<?xml-stylesheet type="text/xsl" href="tapetrack.xslt"?>
<tapetrack_data>
  <item>
    <customer>0001</customer>
    <itemcode>Los Angeles STORAGE_OFFSITE</itemcode>
    <description>CONT Vault Storage Charge</description>
    <count>60</count>
    <cost>0.01</cost>
    <total>0.60</total>
  </item>
  <item>
    <customer>0002</customer>
    <itemcode>Los Angeles STORAGE_OFFSITE</itemcode>
    <description>LT0 Vault Storage Charge</description>
    <count>160</count>
    <cost>0.01</cost>
    <total>1.60</total>
  </item>
  <item>
    <customer>0002</customer>
    <itemcode>Los Angeles MOVE_ONSITE</itemcode>
    <description>LT0 Deliver to Customer </description>
    <count>4</count>
    <cost>10.90</cost>
    <total>10.90</total>
  </item>
</tapetrack_data>
```

Changelog

Cannot load rss feed.

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/cli/tmss10logstatsprocess?rev=1626917369>

Last update: **2025/01/21 22:07**

