

# TMSS10ModifyFlags

TMSS10ModifyFlags adds and removes editable [Flags](#) through the Command Line interface.

## Synopsis

```
TMSS10ModifyFlags [-F new flags] [-S logon string] [-V volume filter] [-c configuration file]
```

## Options

- -F Adds or removes [Flags](#) from [Volumes](#).
- -S The Logon string argument sets the [Server Logon Information](#)
- -V [Volume Filter](#) which can be used to filter the traversal of [Customer](#), [Media](#), [Volume](#), [Repository](#) and [Flag](#) values.
- -c The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of [Customer](#), [Media](#) and [Volumes](#), perform advanced Barcode pre and post processing and route program output to syslogd.

If an argument value starts with the value `FI:`, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named `ACME_volumes` has the content `ACME_*. *`, specifying `FI:/etc/ACME_volumes` will have the same effect as `-V ACME. *. *`. Using `FI:` to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with `*LIST:` then rather than matching the literal value, each record in the file specified as `*LIST:filename` will be tested. If one matches the match will succeed.

2021/06/16 02:14 · Scott Cunliffe

[include page](#)

## Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff.

If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

## Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

## Files

**stdout:** Output Reports.

**stderr:** Diagnostic messages.

## Example

### Command line syntax

```
TMSS10ModifyFlags -S user:-password@server -V "*US04.LT0.*@OFFS" -F E
```

### Output

```

                System: TapeTrack
Report Description: Flag Modification Report
  Production Time: Friday, April 20, 2018 - 09:43:19 (AUS Eastern Standard
Time)
  Report Width: 156 bytes

Seq.   Barcode           Old Flags           New Flags
Message
-----
      1 US04.LT0.000005L6   CnN0tZ             CEnN0tZ
Request OK
      2 US04.LT0.000006L5   CnN0t              CEnN0t
Request OK
      3 US04.LT0.000006L6   CnN0t              CEnN0t
Request OK
      4 US04.LT0.000007L5   CnN0t              CEnN0t
Request OK
      5 US04.LT0.000007L6   CMnNt              CEMnNt
Request OK
      6 US04.LT0.000008L5   CMnNt              CEMnNt
Request OK
      7 US04.LT0.000009L5   CnN0t              CEnN0t
Request OK
      8 US04.LT0.000009L6   CnN0t              CEnN0t
Request OK
-----
-----

```

## Example



Use **Flag** values to add to **Volumes** (eg. E)  
Prefix **Flag** values with **!** to remove from **Volumes** (eg. !E)

To set the E (Encrypted) **Flag** on all LTO tapes:

```
TMSS10ModifyFlags -S tapemaster:-password@localhost -F "E" -V "*.LTO.*"
```

Removing the W (Warning) **Flag** from all **Volumes**

```
TMSS10ModifyFlags -S tapemaster:-password@localhost -F "!W"
```

## Changelog

Cannot load rss feed.

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/cli/tmss10modifyflags?rev=1626752023>

Last update: **2025/01/21 22:07**

