2025/04/05 17:08 1/3 TMSS10MoveLocation

# **TMSS10MoveLocation**

TMSS10MoveLocation puts selected Volumes in a move from one Repository to another.

# **Synopsis**

TMSS10MoveLocation [-C check if volume is assigned to a container] [-M move only if container moving] [-S logon string] [-T move only if assigned container target matches] [-V volume] [-X skip volumes assigned to a container] [-c configuration file] [-e exclude volumes already moving] [-f from repository] [-l apply move lock during move] [-t to repository]

### **Options**

- - C Move Volume only when assigned Container is moving and matches move requirements.
- -M Move only if the assigned Container is moving (requires -C) (default = false).
- -S The Logon string argument sets the Server Logon Information.
- -T Move only if the assigned Container Target matches (requires -C) (default = false).
- V Volume Filter which can be used to filter the traversal of Customer, Media, Volume, Repository and Flag values.
- -X Skip any volumes already assigned to a container.
- c The config file argument specifies the path to the Batch Configuration File. The Batch
  Configuration File allows you to perform advanced traversal of Customer, Media and Volumes,
  perform advanced Barcode pre and post processing and route program output to syslogd.
- -e Exclude any Volumes that are already in a Move Status.
- f Repository to Move Volumes from.
- - l Apply a move-lock to Volumes during move.
- -t Repository to move Volumes to.

If an argument value starts with the value FI:, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME\_volumes has the content ACME\_\*.\*, specifying FI:/etc/ACME\_volumes will have the same effect as -V ACME.\*.\*. Using FI: to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with \*LIST: then rather than matching the literal value, each record in the file specified as \*LIST:filename will be tested. If one matches the match will succeed.

2021/06/16 02:14 · Scott Cunliffe include page

### **Technical Support**

The TapeTrack Software is commercially supported by a full time help desk staff.

If you are experiencing problems or want some advice on how to configure or use the product please

Last update: 2025/01/21 22:07

see the Accessing Technical Support page.

#### **Exit Statuses**

- 1. **zero** Program has ended successfully.
- 2. non-zero Program has not ended successfully.

#### **Environment**

#### **Files**

**stdout:** Output Reports. **stderr:** Diagnostic messages.

stdin: Program input.

### **Example**

#### **Command line syntax**

Move all US02 LTO Volumes with a Barcode ending in 5L6.

```
\label{thm:continuous} TMSS10 Move Location - S user: -password @ server - V "US02.LT0.*5L6" - f "LIBR" - t "OFFS"
```

#### **Output**

```
System: TapeTrack
Report Description: Volumes Moved
       Report Notes: From(LIBR) To(OFFS)
    Production Time: Monday, November 27, 2017 - 12:56:38 (AUS Eastern
Daylight Time)
       Report Width: 92 bytes
                                                   To
Seq.
        Barcode
                              From
Container
                                                   Offsite Vault
      1 US02.LT0.000015L6
                             Library
      2 US02.LT0.000035L6
                             Library
                                                   Offsite Vault
      3 US02.LT0.000065L6
                             Library
                                                   Offsite Vault
      4 US02.LT0.000075L6
                             Library
                                                   Offsite Vault
      5 US02.LT0.000085L6
                             Library
                                                   Offsite Vault
      6 US02.LT0.000095L6
                                                   Offsite Vault
                             Library
      7 US02.LT0.000105L6
                                                   Offsite Vault
                             Library
```

https://rtfm.tapetrack.com/ Printed on 2025/04/05 17:08

2025/04/05 17:08 3/3 TMSS10MoveLocation

8 US02.LT0	0.000115L6	Library	${\tt Offsite}$	Vault
9 US02.LT0	0.000125L6	Library	Offsite	Vault
10 US02.LT0	0.000135L6	Library	Offsite	Vault
11 US02.LT0	0.000145L6	Library	Offsite	Vault
12 US02.LT0	0.000155L6	Library	Offsite	Vault
13 US02.LT0	0.000165L6	Library	Offsite	Vault
14 US02.LT0	0.000175L6	Library	Offsite	Vault
15 US02.LT0	0.000185L6	Library	Offsite	Vault
16 US02.LT0	0.000195L6	Library	Offsite	Vault
17 US02.LT0	0.000205L6	Library	Offsite	Vault
18 US02.LT0	0.000215L6	Library	Offsite	Vault
19 US02.LT0	0.000225L6		Offsite	Vault
20 US02.LT0	0.000235L6	Library	Offsite	Vault
21 US02.LT0	0.000245L6	Library	Offsite	Vault
22 US02.LT0	0.000255L6	Library	Offsite	Vault
23 US02.LT0	0.000265L6	Library	Offsite	Vault
24 US02.LT0	0.000275L6	Library	Offsite	Vault
25 US02.LT0	0.000285L6	Library	Offsite	Vault
26 US02.LT0	0.000295L6	Library	Offsite	Vault
27 US02.LT0	0.000305L6	Library		
28 US02.LT0	0.000315L6	Library	Offsite	Vault

# Changelog

Cannot load rss feed.

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/cli/tmss10movelocation?rev=1631586552

Last update: 2025/01/21 22:07

