

# TMSS10Reconcile

TMSS10Reconcile performs a batch reconciliation on a [Repository](#).

## Synopsis

```
TMSS10Reconcile [-B bypass confirmation] [-C certify] [-F don't fix surplus volumes] [-R Subject repository] [-S logon string] [-V volume filter] [-a add fully qualified volumes] [-c configuration file] [-d certificate description] [-e csv error file location] [-l input scan list] [-m minimum loaded volumes to continue]
```

## Options

- -A Attribute Index (default=0)
- -B Bypass confirming [Volume](#) at Target [Repository](#).
- -C Certify [Volumes](#) (default = false).
- -F Don't fix surplus [Volumes](#) by moving them to the Scan [Repository](#) and back (default = false).
- -G Number of grace hours on confirmed Volumes before audit flag added (default = 24 hours)
- -R Subject [Repository](#) for reconciliation.
- -S The Logon string argument sets the [Server Logon Information](#).
- -V [Volume Filter](#) which can be used to filter the traversal of [Customer](#), [Media](#), [Volume](#), [Repository](#) and flag values.
- -a Add any fully qualified [Volume](#) in the scanfile not in TapeTrack (default = false).
- -c The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of [Customer](#), [Media](#) and [Volumes](#), perform advanced Barcode pre and post processing and route program output to syslogd.
- -d Certificate description.
- -e CSV error file location.
- -l Input scan file list to reconcile against.
- -m Minimum loaded [Volumes](#) to continue to execute process (default = 10).

If an argument value starts with the value **FI:**, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME\_volumes has the content ACME\_\*.\*, specifying **FI:/etc/ACME\_volumes** will have the same effect as **-V ACME.\*.\***. Using **FI:** to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with **\*LIST:** then rather than matching the literal value, each record in the file specified as **\*LIST:filename** will be tested. If one matches the match will succeed.

2021/06/16 02:14 · Scott Cunliffe

[include page](#)

# Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

## Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

## Environment

## Files

**stdout:** Output Reports.

**stderr:** Diagnostic messages.

**stdin:** Program input.

## Example

### Command line syntax

```
TMSS10Reconcile -S user:-password@server -R "OFFS" -l  
"C:\Users\GazillaByte\reconcile_2017-11-29.txt" -V "US04.LT0.*"
```

### Output

The output of the TapeTrack Reconciliation program is described in detail on the page [Reconciliation Report](#)

## See Also

[Command Line Utility Troubleshooting and Diagnosis](#)

[Changelog](#)

Cannot load rss feed.

From:  
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**



Permanent link:  
<https://rtfm.tapetrack.com/cli/tmss10reconcile>

Last update: **2025/07/04 04:48**