# TMSS10Reconcile

# **Synopsis**

TMSS10Reconcile [-B bypass confirmation] [-C certify] [-F don't fix surplus volumes] [-R Subject repository] [-S logon string] [-V volume filter] [-a add fully qualified volumes] [-c configuration file] [-d certificate description] [-e csv error file location] [-l input scan list] [-m minimum loaded volumes to continue]

### **Description**

TMSS10Reconcile performs a batch reconciliation on a Repository.

### **Options**

- - A Attribute Index (default=0)
- -B Bypass confirming Volume at Target Repository.
- -C Certify Volumes (default = false).
- -F Don't fix surplus Volumes by moving them to the Scan Repository and back (default = false).
- -G Number of grace hours on confirmed Volumes before audit flag added (default = 24 hours)
- -R Subject Repository for reconciliation.
- -S The Logon string argument sets the Server Logon Information.
- -V Volume Filter which can be used to filter the traversal of Customer, Media, Volume, Repository and flag values.
- -a Add any fully qualified Volume in the scanfile not in TapeTrack (default = false).
- -c The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of Customer, Media and Volumes, perform advanced Barcode pre and post processing and route program output to syslogd.
- -d Certificate description.
- -e CSV error file location.
- -l Input scan file list to reconcile against.
- -m Minimum loaded Volumes to continue to execute process (default = 10).

### **Technical Support**

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

## Last update: 2025/01/21 22:07

### **Exit Statuses**

- 1. zero Program has ended successfully.
- 2. non-zero Program has not ended successfully.

### **Environment**

#### **Files**

**stdout:** Output Reports. **stderr:** Diagnostic messages.

stdin: Program input.

### **Example**

#### **Command line syntax**

```
TMSS10Reconcile -S user:-password@server -R "0FFS" -l "C:\Users\GazillaByte\reconcile_2017-11-29.txt" -V "US04.LT0.*
```

#### **Output**

The output of the TapeTrack Reconciliation program is described in detail on the page Reconciliation Report

## **Changelog**

Cannot load rss feed.

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/cli/tmss10reconcile?rev=1618986382

Last update: 2025/01/21 22:07



https://rtfm.tapetrack.com/ Printed on 2025/04/19 02:35