

TMSS10ValidateBarcode

Synopsis

TMSS10ValidateBarcode [-C Customer-ID] [-M Media-ID] [-S logon string]

Description

TMSS10ValidateBarcode will parse a list of volume Barcodes, outputting the Barcode rule the Barcode will be parsed under if valid.

Options

- -C Default Customer-ID.
- -M Default Media-ID
- -S The Logon string argument sets the [Server Logon Information](#)

If an argument value starts with the value FI:, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME_volumes has the content ACME_*.*, specifying FI:/etc/ACME_volumes will have the same effect as -V ACME.*.*. Using FI: to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with *LIST: then rather than matching the literal value, each record in the file specified as *LIST:filename will be tested. If one matches the match will succeed.

2021/06/16 02:14 · Scott Cunliffe

[include page](#)

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.

stderr: Diagnostic messages.

stdin: Program input.

Example

Command line syntax

```
TMSS10ValidateBarcode -S user:-password@server -C "US02" -M "LT0"
```

Once you have run the above code, enter in the Barcodes to be parsed either manually, via cut and paste or Barcode scanner.


Output

```

                System: TapeTrack
Report Description: Barcode Parse Report
  Production Time: Monday, November 27, 2017 - 11:18:23 (AUS Eastern
Daylight Time)
  Report Width: 157 bytes

Seq.   Barcode           C-ID M-ID V-ID           Rule Rule Description
Result
-----
-----
111111L6
   2 111111L6           US02 LT0   111111L6   18 Generic *
Request OK
1234567890L6
   3 1234567890L6      US02 LT0   1234567890 18 Generic *
Request OK

```

 Note the truncation of volume Barcodes over 10 characters.

See Also

[Command Line Utility Troubleshooting and Diagnosis](#)

Changelog

Cannot load rss feed.

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/cli/tmss10validatebarcode>

Last update: **2025/07/04 04:49**

