

TMSS10ValidateBarcode

Synopsis

```
TMSS10ValidateBarcode [-C customer ID] [-M media ID] [-S logon string]
```

Description

TMSS10ValidateBarcode will parse a list of volume barcodes, outputting the barcode rule the barcode will be parsed under if valid.

Options

- -C Default Customer ID.
- -M Default Media ID
- -S The logon string argument sets the [Server logon information](#)

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.

stderr: Diagnostic messages.

stdin: Program input.

Example

Command line syntax

```
TMSS10ValidateBarcode -S user:-password@server -C "US02" -M "LT0"
```

Once you have run the above code, enter in the barcodes to be parsed either manually, via cut and paste or barcode scanner.


Output

```

System: TapeTrack
Report Description: Barcode Parse Report
Production Time: Monday, November 27, 2017 - 11:18:23 (AUS Eastern
Daylight Time)
Report Width: 157 bytes

Seq. Barcode C-ID M-ID V-ID Rule Rule Description
Result
-----
-----
111111L6
  2 111111L6 US02 LT0 111111L6 18 Generic *
Request OK
1234567890L6
  3 1234567890L6 US02 LT0 1234567890 18 Generic *
Request OK

```

 Note the truncation of volume barcodes over 10 characters.

From: <https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link: <https://rtfm.tapetrack.com/cli/tmss10validatebarcode?rev=1511742603>

Last update: **2025/01/21 22:07**

