TMSS10VolumeDelete

Deletes Volumes from the database.

Synopsis

```
TMSS10VolumeDelete [-S logonstring] [-V volumefilter] [-c configfile] [-l
Live mode] [-r target repository]
```

Description

TMSS10VolumeDelete deletes Volumes from the database using filters and/or configuration file.

Options

TMSS10VolumeRename command options:

- -S The logon string argument sets the Server logon information.
- -V The volume filter argument sets the Volume Filter which can be used to filter the traversal of Customer, Media and Volume values. The format of this filter is c.m.v@r, where c is Customer-ID filter, m is Media-ID filter, v is Volume-ID filter and r is Repository-ID filter. To process only volumes not in Repository ACME, "*.*.*@!(ACME).
- * -c The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of Customer, Media and Volumes, perform advanced barcode pre and post processing and route program output to syslogd. Configuration File capabilities vary from program to program but the syntax remains the same. In the event that logic is not supported it will simply be ignored.
- -l Live mode (default = true.
- -r Target Repository Filter.

From:
https://rtfm.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/cli/tmss10volumedelete?rev=1551737226

Last update: **2025/01/21 22:07**