2025/12/01 15:51 1/2 TMSS10VolumeDelete

TMSS10VolumeDelete

Deletes Volumes from the database.

Synopsis

TMSS10VolumeDelete [-S logonstring] [-V volumefilter] [-c configfile] [-l Live mode] [-r target repository]

Description

TMSS10VolumeDelete deletes Volumes from the database using filters and/or configuration file.

Options

TMSS10VolumeRename command options:

- -S The Logon string argument sets the Server Logon Information.
- -V The volume filter argument sets the Volume Filter which can be used to filter the traversal of Customer, Media and Volume values. The format of this filter is c.m.v@r, where c is Customer-ID filter, m is Media-ID filter, v is Volume-ID filter and r is Repository-ID filter. To process only volumes not in Repository ACME, "*.*.*@!(ACME).
- * c The config file argument specifies the path to the Batch Configuration File. The Batch
 Configuration File allows you to perform advanced traversal of Customer, Media and Volumes,
 perform advanced barcode pre and post processing and route program output to syslogd.
 Configuration File capabilities vary from program to program but the syntax remains the same.
 In the event that logic is not supported it will simply be ignored.
- -1 Live mode (default = true.
- - r Target Repository Filter.

Exit Status

- 1. **zero** Program has ended successfully.
- 2. **non-zero** Program has not ended successfully.

Environment

Files

stdout Output Reports.

• stderr Diagnostic messages.

Examples

See TMSS10VolumeDelete Examples

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/cli/tmss10volumedelete?rev=1578528486

Last update: 2025/01/21 22:07



https://rtfm.tapetrack.com/ Printed on 2025/12/01 15:51