2025/05/11 08:12 1/3 TMSS10VolumeRename

# TMSS10VolumeRename

This program renames a volume or list of volumes

# **Synopsis**

TMSS10VolumeRename [-S logonstring] [-V volumefilter] [-C new Customer ID] [-M new Media ID] [-N new Volume ID] [-c configfile] [-l Live mode]

# **Description**

TMSS10VolumeRename will rename the volume ID of a current volume or list of volumes, keeping history records associated with that volume/s.

## **Options**

TMSS10VolumeRename command options:

- -S The logon string argument sets the Server logon information.
- -V The volume filter argument sets the Volume Filter which can be used to filter the traversal of Customer, Media and Volume values. The format of this filter is c.m.v@r, where c is Customer-ID filter, m is Media-ID filter, v is Volume-ID filter and r is Repository-ID filter. To process only volumes not in Repository ACME, "\*.\*.\*@!(ACME).
- - C New Customer ID.
- -M New Media ID.
- - N New Volume ID.
- c The config file argument specifies the path to the Batch Configuration File. The Batch
  Configuration File allows you to perform advanced traversal of Customer, Media and Volumes,
  perform advanced barcode pre and post processing and route program output to syslogd.
  Configuration File capabilities vary from program to program but the syntax remains the same.
  In the event that logic is not supported it will simply be ignored.
- - l Live mode.

### **Exit Status**

- 1. **zero** Program has ended successfully.
- non-zero Program has not ended successfully.

## **Environment**

### Last update: 2025/01/21 22:07

### **Files**

- stdout Output Reports.
- stderr Diagnostic messages.

## **Examples**

### **Renaming Volume - New Volume ID**

Renaming a single volume to assign a new volume ID, for example if you have a typo in the volume ID you want to fix without losing the historical records accumulated.

To rename volume US04.LT0.111211L6 to US04.LT0.111111L6

### **Command line syntax**

```
TMSS10VolumeRename -S doco:-doco@localhost -V "US04.LT0.111211L6" -N "111111L6" -l
```

### **Output**

```
System: TapeTrack
Report Description: Volume Rename Report
Production Time: Wednesday, March 21, 2018 - 10:20:18 (AUS Eastern
Daylight Time)
Report Width: 111 bytes

Seq. Old Identity New Identity Messages

1 US04.LT0.111211L6 US04.LT0.111111L6 Request OK
```

### Renaming Volume - Same Volume ID, New Customer ID

https://rtfm.tapetrack.com/ Printed on 2025/05/11 08:12

2025/05/11 08:12 3/3 TMSS10VolumeRename

#### **Command line syntax**

```
TMSS10VolumeRename -S doco:-doco@localhost -V "US04.LT0.123456L6" -N "*" -C "US03" -l
```

### **Output**

```
System: TapeTrack
Report Description: Volume Rename Report
Production Time: Wednesday, March 21, 2018 - 10:20:18 (AUS Eastern
Daylight Time)
Report Width: 111 bytes

Seq. Old Identity New Identity Messages

1 US04.LT0.123456L6 US03.LT0.123456L6 Request OK
```

# **Changelog**

Cannot load rss feed.

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/cli/tmss10volumerename?rev=1531420099

Last update: **2025/01/21 22:07** 

