


Overview

Volume Flags represent one or more Boolean statuses of a single tape volume.

Depending on the respective flag, the flag may be automatically set, or may be set and unset by the user.

These flags can be used to filter tapes by status, for instance, scratch tapes, or encrypted tapes, or may be used together to facilitate filtering on all scratch tapes, that are not encrypted.



Flag Definitions

Flag Value	Description	Settable
A	Volume has a Container Security Tag assigned.	No
a	Volume has failed a Physical Audit or a Logical Audit (Set by Reconciliation).	Yes
B	Volume is a Container.	No
C	Volume is confirmed in its current Repository.	No
c	Volume is part of a Consignment.	No
D	Volume has a Move Date.	No
d	Volume Move Date is in the past.	No
E	Volume is encrypted.	Yes
F	Volume has been set as a Favorite	No
G	Volume has missed a reporting deadline.	Yes
H	Volume Move Date is a Holiday.	No
h	Volume is hidden (ghosted).	Yes
I	Volume is moving internally (from one Slot to another in the same Repository).	No
K	Volume has been Picked-Up.	Yes
L	Volume has an update lock and cannot be updated by anyone other than the tapemaster User .	Yes
I	Volume has a move lock and cannot be moved.	Yes

Flag Value	Description	Settable
M	Volume is moving from one Repository to another.	No
m	Volume has a Home Slot.	No
N	Volume has a Description.	No
n	Volume has no Slot assigned.	No
O	Volume is in the Primary Offsite Repository.	No
o	Volume is overdue at its Target Repository.	No
P	Volume has been set as Move Pending as its Move Date has been exceeded (Set by TMSS10MovePending).	Yes
Q	Volume has been flagged as unhealthy by a VeriTape system.	Yes
r	Volume has been requested back from a Third Party.	Yes
S	Volume always uses Simple Management .	Yes
t	Do not assign a Slot to this Volume.	Yes
U	Volume has been scanned out of the current Repository using either TapeTrack Lite or TapeTrack Check Point.	Yes
u	Volume has been flagged as a duplicate.	Yes
W	Volume has a warning (has moved back to its original Repository without having been confirmed at its destination).	Yes
X	Volume has been Audit-Scanned.	Yes
Z	Volume is Scratch.	Yes

Using Flags

TapeTrack uses many of the volume flags internally to pass information from one program to another, but flags can also be used to filter information for reporting purposes.

Using Flags for Reporting

Setting and Unsetting Flags

Some volume flags can be set and unset by performing operations on the respective tape volume, for instance, when you move a volume, the tape will get a move flag, and when you confirm a volume the move flag will be removed.

Other flags can only be set and unset by the user requesting that they change, and the remaining flags are a hybrid that are set by an activity, and then unset manually.

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/common/volume_flags?rev=1503707657

Last update: **2025/01/21 22:07**

