

NetWorker Sync Cookbook

[NetWorker](#) is a Dell EMC backup solution and is available for Linux, Windows, macOS, NetWare, OpenVMS and Unix.

The mminfo command

The mminfo command reports information about NetWorker media and save sets.

To get a report that is suitable for the TapeTrack Sync command, the following minimum arguments should be used:

```
mminfo -xc, -a -r "volume,barcode,family,type,location,pool" > report.csv
```

Example mminfo output

```
volume,barcode,family,type,location,pool
000000L6,000000L6,tape,LTO,Offsite,weekly_full
000001L6,000001L6,tape,LTO,Offsite,weekly_full
000002L6,000002L6,tape,LTO,Offsite,weekly_full
000003L6,000003L6,tape,LTO,Offsite,weekly_full
000004L6,000004L6,tape,LTO,Offsite,weekly_full
000005L6,000005L6,tape,LTO,Offsite,weekly_full
000006L6,000006L6,tape,LTO,Offsite,weekly_full
000007L6,000007L6,tape,LTO,Offsite,weekly_full
```

Post-processing



You will need to install the [TapeTrack Sync software](#) to complete these instructions.

Barcodes

It possible for NetWorker barcodes to be missing the LTO L-Suffix.

It is always recommended that where possible volumes be loaded into TapeTrack with their L-Suffix, and this suffix can be established by:

1. The Media ID value if it includes the suffix.

2. Adding an appropriate suffix to the Media ID based upon the value of the Media Type field.
3. Adding an appropriate suffix based upon the range of the Media ID.
4. Using TapeTrack's Constructive Barcode feature.

Synchronization

Synchronization with TapeTrack is performed by calling the [TMSS10Sync](#) command line program, along with:

1. The CSV file produced by pre-processing the mminfo output.
2. Command line arguments that instruct the program how to process volumes.
3. A synchronization definition file that instructs the program how to interpret the mminfo output.

To interpret the output in the file we use a definition file (default.ttidef) which reads the data in the Networker file, line by line, and parses the information which TMSS10Sync then uses to update the volumes location (and other data as specified) in the TapeTrack Server. It is best practice to write the definition file in a program like Notepad or Vi to ensure it is plain text and has no hidden control characters.

default.ttidef

default.ttidef file sample with code to:

- Set CSV file delimiter (2)
- Exclude any string that starts with barcode (5)
- Set customer ID to US01 (8)
- Set media ID to LTO (9)
- Set default repository to LIBR (12)
- extract volume ID from column 1, length 8 characters (15)
- extract volume description from column 6, length 50 characters (18)
- If description contains the string "Offsite" set repository to **OFFS** (21)

```
# Set CSV delimiter
SetCSVDelimiter(",");

# Skip any line that begins with barcode (header)
AddString(EXCLUSION, 0, "barcode*");

# Set customer ID and media ID to sync with
setLiteral(CUSTOMER, "US01");
setLiteral(MEDIA, "LTO");

# All volumes initially set to library
setLiteral(REPOSITORY, "LIBR");

# Extract Volume ID from column 1 (up to eight characters long)
```

```
Extract(VOLUME, 1, 8, 0);

# Extract volume Description from column 6 (up to fifty characters long)
Extract(DESCRIPTION, 6, 50, 0);

# Send any volume from the pool **offsite** to OFFS repository
AddTranslation2(REPOSITORY, DESCRIPTION, "Offsite*", "OFFS");
```

Sync Information

Create a batch file with code to run Networkers mminfo command and then TMSS10Sync with the required parameters to input the report.csv file and default.ttidef file. Running with the -M command will place the Sync in dump mode, which allows you to check the output from the process without executing any alterations in the TapeTrack Server.

Sample batch file to run mminfo, pass the information to TMSS10Sync and output a dump of information.

```
mminfo -xc, -a -r "volume,barcode,family,type,location,pool" > report.csv
TMSS10Sync -M < report.csv > stdout.txt 2> stderr.txt
```

When you are happy with the output, remove the -M attribute and insert -S attribute and access credentials for the TMSS10Sync command line. Adding an attribute -a will add any new volumes in NetWorker not present in TapeTrack.

```
mminfo -xc, -a -r "volume,barcode,family,type,location,pool" > report.csv
TMSS10Sync -S user:-password@server -a < report.csv > stdout.txt 2>
stderr.txt
```

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/cookbook/networker?rev=1537327108>

Last update: **2025/01/21 22:07**

