## Overview

When using the TapeTrack Desktop Software you will have to have one or more TapeTrack Framework Server entries defined so that you can connect to a server endpoint.

This can be done in the following ways:

- 1. Adding a connection interactively.
- 2. Adding a connection to the Configuration File.
- 3. Clicking on a URL.
- 4. Clicking a Windows Registry File.



When using TapeTrack TapeMaster that was installed as part of the TapeTrack Framework Server installation, an entry for localhost will be automatically added by the installer.

## **Prerequisites**

To configure a server you will need the following information:

- 1. The server IP address or DSN name.
- 2. The server port (usually 5000).
- 3. If you are connecting via a HTTP Proxy:
  - $\circ\,$  The proxy IP address or DNS Name.
  - The proxy port
  - $\circ$  The proxy user name (if authentication is required)
  - The proxy password (if authentication is required)

## Adding a connection interactively

Last update: 2025/01/21 22:07

Logon	Connection to this TapeTrack Server is restricted to authorized users only. Please select your TapeTrack Server and enter your credentials. All access attempts and successful connections will be recorded. Server Local Server Clocal Select a Server or click the button above to add a new Server. User or Email No MD5 (required for Active Directory authentication) Save User History	×
peTrack Options	OK Car	ncel

TapeTrack Se	ervers 📓 Advanced Connection Settings				
Short Name	Address	IP	Port	Proxy	Response
Local	localhost	127.0.0.1	5000	No	OK (36.00 ms)
	Add N				
	Delete				
	Properties				
	Create Desktop Shortcut				
					OK Cancel Apply

Server Information	×
Server Name My Server	
Server Address tapetrack.mycompany.com	
Server Port 5000	
Use HTTP Proxy False	
Use Single Sign-On False	
Server Address	
TapeTrack Server name or IP address	
Example 'tapetrack.mydomain.com' or '192.168.1.10'	
OK Cancel	
Tana Tanà Ordina	
TapeTrack Options	×
I Tape Track Servers Advanced Connection Settings	
HTTP Proxy Settings	
Address proxy.gazillabyte.local	
Port 3128 🖨	
User ID gnicol	
Password ••••••	
Automatically Detect HTTP Proxy	
Automatically Detect III II Hoxy	

×

## Adding a connection with the Configuration File

Each TapeTrack Desktop Program has a configuration file that is kept in

servers =

```
{
   Server1 = { host = "odpapi-test.tapetrack.com"; };
   Server2 = { host = "odpapi-test.tapetrack.com"; port=433; proxy=true; };
};
```

From: https://rtfm.tapetrack.com/ - **TapeTrack Documentation** 

Permanent link: https://rtfm.tapetrack.com/desktop/adding\_connection?rev=1504547506



Last update: 2025/01/21 22:07