

# AddString

Add a special string such as an exclusion or header string.

## Phase

This instruction is used by the TapeTrack Import Engine.

## Syntax

```
AddString(type, offset, filter); string type; integer offset; string filter;
```

**type** The special string type of one of the following:

1. HEADER A string that represents the first record of a heading section. 2. EXCLUSION A string that represents the a record that should be excluded from all further processing (skipped). 3. START A string that represents when processing should start. If there is no start string specified processing will start at the first record. 4. END A string that represents when processing should temporarily stop. Processing will recommence at the next START record. 5. TERMINATE A string that represents when processing should permanently stop. No processing will be done past this point, even if a START record is encountered.

**offset** The zero based offset within the record at which the filter should be applied.

**filter** A filter value for comparison with the processed string.

## Examples

Example A.22. AddString: Define a header (ANSI page break) with 7 records, skip records not starting with an integer and terminate processing at the first blank record  
AddString(H HEADER, 0, "1\*");  
SetHeaderCount(7); AddString(EXCLUSION, 0, "![0-9]\*"); AddString(TERMINATE, 0, " \*");

From:

<https://rtfm.tapetrack.com/> - TapeTrack Documentation

Permanent link:

<https://rtfm.tapetrack.com/engine/import/addstring?rev=1534198097>

Last update: **2025/01/21 22:07**

