

AddString

Add a special string such as an exclusion or header string.

Phase

This instruction is used by the TapeTrack Import Engine.

Syntax

```
AddString(type, offset, filter);
```

string type; integer offset; string filter;

type The special string type of one of the following:

1. 1. **HEADER** A string that represents the first record of a heading section.
2. 2. **EXCLUSION** A string that represents the a record that should be excluded from all further processing (skipped).
3. 3. **START** A string that represents when processing should start. If there is no start string specified processing will start at the first record.
4. 4. **END** A string that represents when processing should temporarily stop. Processing will recommence at the next **START** record.
5. 5. **TERMINATE** A string that represents when processing should permanently stop. No processing will be done past this point, even if a **START** record is encountered.
6. **offset** The zero based offset within the record at which the filter should be applied.
7. **filter** A filter value for comparison with the processed string.

Examples

Example A.22. AddString: Define a header (ANSI page break) with 7 records, skip records not starting with an integer and terminate processing at the first blank record `AddString(HEADER, 0, "1*"); SetHeaderCount(7); AddString(EXCLUSION, 0, "![0-9]*"); AddString(TERMINATE, 0, "*");`

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/engine/import/addstring?rev=1534198201>

Last update: **2025/01/21 22:07**

