

AddString

Add a special string such as an exclusion or header string.

Phase

This instruction is used by the TapeTrack Import Engine.

Syntax

```
AddString(type, offset, filter);
```

```
string type; integer offset; string filter;
```

type The special string type of one of the following:

1. HEADER A string that represents the first record of a heading section.
2. EXCLUSION A string that represents the a record that should be excluded from all further processing (skipped).
3. START A string that represents when processing should start. If there is no start string specified processing will start at the first record.
4. END A string that represents when processing should temporarily stop. Processing will recommence at the next START record.
5. TERMINATE A string that represents when processing should permanently stop. No processing will be done past this point, even if a START record is encountered.
6. offset The zero based offset within the record at which the filter should be applied.
7. filter A filter value for comparison with the processed string.

Examples

Example A.22. AddString: Define a header (ANSI page break) with 7 records, skip records not starting with an integer and terminate processing at the first blank record
AddString(H HEADER, 0, "1*");
SetHeaderCount(7); AddString(EXCLUSION, 0, "![0-9]*"); AddString(TERMINATE, 0, " *");

From:

<https://rtfm.tapetrack.com/> - TapeTrack Documentation

Permanent link:

<https://rtfm.tapetrack.com/engine/import/addstring?rev=1534198201>

Last update: 2025/01/21 22:07

