

AddString

Add a special string such as an exclusion or header string.

Phase

This instruction is used by the TapeTrack Import Engine.

Syntax

AddString(type, offset, filter);

string type;

integer offset;

string filter;

- type The special string type of one of the following:
 1. **HEADER** A string that represents the first record of a heading section.
 2. **EXCLUSION** A string that represents the a record that should be excluded from all further processing (skipped).
 3. **START** A string that represents when processing should start. If there is no start string specified processing will start at the first record.
 4. **END** A string that represents when processing should temporarily stop. Processing will recommence at the next START record.
 5. **TERMINATE** A string that represents when processing should permanently stop. No processing will be done past this point, even if a START record is encountered.
- offset The zero based offset within the record at which the filter should be applied.
- filter A filter value for comparison with the processed string.

Examples

Example A.22. AddString: Define a header (ANSI page break) with 7 records, skip records not starting with an integer and terminate processing at the first blank record AddString(HEADER, 0, "1*"); SetHeaderCount(7); AddString(EXCLUSION, 0, "[!([0-9]*"); AddString(TERMINATE, 0, " *");

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/engine/import/addstring?rev=1534264396>

Last update: **2025/01/21 22:07**



