2025/05/06 05:21 1/2 AddString

AddString

Add a special string such as an exclusion or header string.

Phase

This instruction is used by the TapeTrack Import Engine.

Syntax

```
AddString(type, offset, filter);

string type;

integer offset;
```

string filter;

type The special string type of one of the following:

- 1. **HEADER** A string that represents the first record of a heading section.
- 2. **EXCLUSION** A string that represents the a record that should be excluded from all further processing (skipped).
- 3. **START** A string that represents when processing should start. If there is no start string specified processing will start at the first record.
- 4. **END** A string that represents when processing should temporarily stop. Processing will recommence at the next START record.
- 5. **TERMINATE** A string that represents when processing should permanently stop. No processing will be done past this point, even if a START record is encountered.

```
offset The zero based offset within the record at which the filter should be applied. filter A filter value for comparison with the processed string.
```

Example

AddString: Define a header (ANSI page break) with 7 records, skip records not starting with an integer and terminate processing at the first blank record

```
AddString(HEADER, 0, "1*");
SetHeaderCount(7);
AddString(EXCLUSION, 0, "!([0-9]*");
AddString(TERMINATE, 0, " *");
```

Last update: 2025/01/21 22:07

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/engine/import/addstring?rev=1534264862

Last update: 2025/01/21 22:07



https://rtfm.tapetrack.com/ Printed on 2025/05/06 05:21