

AddString

Add a special string such as an exclusion or header string.

Phase

This instruction is used by the TapeTrack Import Engine.

Syntax

```
AddString(type, offset, filter);
```

Variable	Type	Description	Min Length	Max Length	Min Value	Max Value
type	String	The special string type from the below Type Values table	1	10		
offset	Integer	The zero based offset within the record at which the filter should be applied.	1	10	-214748364	2147483647
filter	String	A filter value for comparison with the processed string.	1	256		

Type Values

Value	Description
HEADER	A string that represents the first record of a heading section.
EXCLUSION	A string that represents the a record that should be excluded from all further processing (skipped).
START	A string that represents when processing should start. If there is no start string specified processing will start at the first record.
END	A string that represents when processing should temporarily stop. Processing will recommence at the next START record.
TERMINATE	A string that represents when processing should permanently stop. No processing will be done past this point, even if a START record is encountered.

Example

AddString: Define a header (ANSI page break) with 7 records, skip records not starting with an integer and terminate processing at the first blank record

```
AddString(HEADER, 0, "1*");
SetHeaderCount(7);
AddString(EXCLUSION, 0, "![0-9]*");
AddString(TERMINATE, 0, " *");
```

[import engine](#), [sync engine](#)

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/engine/import/addstring?rev=1583364539>

Last update: **2025/01/21 22:07**

