

# AddTranslation2FromFile

Translate the value of a field based upon the value of another field, where the other field value can be loaded multiple times using the contents of a file.

## Phase

This instruction is used by the TapeTrack Import Engine.

## Syntax

```
AddTranslation2FromFile(field, field2, filterfile, translation);
```

Variable	Type	Description	Min Length	Max Length
field	String	The field to be translated.	1	128
field2	String	The field to be compared.	1	128
filterfile	String	A file containing filter values to compare against the current field value.	1	256
translation	String	The new value of the field. This can either be a new literal value, or the original value with a prefix or suffix. To represent the current value use an asterisk ("*").	1	256



See the notes for [Add Translation2](#).

## Example

Append L3 to each VOLUME field if the value of the MEDIA matches a pattern within a record of c:\data\LTO3Volumes.txt.

```
AddTranslation2FromFile(VOLUME, MEDIA, "c:\data\LTO3Volumes.txt", "*L3");
```

## See Also

[Import Engine Functions](#)

[Sync Engine Fields](#)

[TMSS10Sync](#)

[import engine](#), [sync engine](#), [update doco](#)

From:  
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:  
<https://rtfm.tapetrack.com/engine/import/addtranslation2fromfile>

Last update: **2025/01/21 22:07**

