

AddTranslation2FromFile

Translate the value of a field based upon the value of another field, where the other field value can be loaded multiple times using the contents of a file.

Phase


This instruction is used by the TapeTrack Import Engine.

Syntax

```
AddTranslation2FromFile(field, field2, filterfile, translation);
```

string field;
string field2;
string filterfile;
string translation;

field	The field to be translated.
field2	The field to be compared.
filterfile	
translation	The new value of the field. This can either be a new literal value, or the original value with a prefix or suffix. To represent the current value use an asterisk ("*").


 See the notes section for [Add Translation2](#).

Example

Append L3 to each VOLUME field if the value of the MEDIA matches a pattern within a record of c:\data\LT03Volumes.txt.

```
AddTranslation2FromFile(VOLUME, MEDIA, "c:\data\LT03Volumes.txt", "*L3");
```

[import engine](#), [sync engine](#), [update doco](#)



Last update:
2025/01/21
22:07

engine:import:addtranslation2fromfile <https://rtfm.tapetrack.com/engine/import/addtranslation2fromfile?rev=1582513810>

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/engine/import/addtranslation2fromfile?rev=1582513810>



Last update: **2025/01/21 22:07**