

# Extract

Extract a field from a record, CSV element or SQL field.

## Phase

This instruction is used by the TapeTrack Import Engine.

## Syntax

```
Extract(field, offset, length, record);
```

*string field;*

*Integer offset;*

*Integer length;*

*Integer record;*

| Variable | Type    | Description  | Min Length | Max Length | Min Value  | Max Value  |
|----------|---------|--|------------|------------|------------|------------|
| field    | String  | The field to be set by this extraction.  | 1          | 128        |            |            |
| offset   | Integer | The zero based offset of the data to be extract, or the element index of a CSV element or SQL element. In the event that the data being processed is CSV based, a value of zero indicates that the raw CSV string should be extracted rather than an individual CSV element. | 1          | 10         | -214748364 | 2147483647 |
| length   | Integer | The length of the data to be extracted if the data is text based, or the maximum data length for CSV or SQL data.  | 1          | 10         | -214748364 | 2147483647 |
| record   | Integer | The record within a header, if the value is non-zero and the data is text based. A record that is not a header if the value is zero and the data is text based. For CSV and SQL data this argument is ignored.   | 1          | 10         | -214748364 | 2147483647 |

## Example

**Extract: Extract VOLUME field from offset 10, length 6 of the body of a report.**

```
Extract(VOLUME, 10, 6, 0);
```

**Extract: Extract VOLUME field from the 2nd element of a CSV file.**

```
SetCSVDelimiter(",");
```

```
Extract(VOLUME, 2, 6, 0);
```

**Extract: Extract REPOSITORY field from offset 70, length 4 of the 3rd record of a header.**

```
Extract(REPOSITORY, 70, 4, 3);
```

[import engine](#), [sync engine](#)

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/engine/import/extract?rev=1583978933>

Last update: **2025/01/21 22:07**

