

# AddSkipOnRepositoryChange

Skip the update of a Volume if the Current or Target Repository is equal to a filter value.

## Phase

This instruction is used by the TapeTrack Synchronization Engine.

## Syntax

**AddSkipOnRepositoryChange**(*proposed*, *target*, *current*);

```
string proposed;  
string target;  
string current;
```

<i>proposed</i>	Filter value representing the proposed change to the Target Repository.
<i>target</i>	Filter value representing the current Target Repository value.
<i>current</i>	Filter value representing the current Current Repository Value

## Example

Skip an update if the proposed change is HOLD and the current target repository is LIBR.

```
#  
# Skip an update if the proposed change is HOLD, the target Repository is  
LIBR and the current is any.  
#  
AddSkipOnRepositoryChange("HOLD", "LIBR", "*");
```

Skip an update if the proposed change is HOLD, the target Repository is LIBR and the current Repository is OFFS, LEGL or DEST.

```
#  
# Skip an update if the proposed change is HOLD, the target Repository is  
LIBR and the current is any.  
#  
AddSkipOnRepositoryChange("HOLD", "LIBR", "*"(OFFS|LEGL|DEST));
```

Skip any update that attempts to move a Volume out of Current Repository DEST.

Last update:

2025/01/21 engine:sync:addskiponrepositorychange https://rtfm.tapetrack.com/engine/sync/addskiponrepositorychange?rev=1566528443  
22:07

```
#  
# Skip an update if the proposed change is HOLD, the target Repository is  
LIBR and the current is any.  
#  
AddSkipOnRepositoryChange("*", "*", "DEST");
```

From:

<https://rtfm.tapetrack.com/> - TapeTrack Documentation



Permanent link:

<https://rtfm.tapetrack.com/engine/sync/addskiponrepositorychange?rev=1566528443>

Last update: **2025/01/21 22:07**