

AddSkipOnRepositoryChange

Skip the update of a Volume if the Current or Target Repository is equal to a filter value.

Phase

This instruction is used by the TapeTrack Synchronization Engine.

Syntax

AddSkipOnRepositoryChange(*proposed*, *target*, *current*);

string *proposed*;
string *target*;
string *current*;

| | |
|----------|---|
| proposed | Filter value representing the proposed change to the Target Repository. |
| target | Filter value representing the current Target Repository value. |
| current | Filter value representing the current Current Repository Value |

Example

Skip an update if the proposed change is HOLD and the current target repository is LIBR.

```
#  
# Skip an update if the proposed change is HOLD, the target Repository is  
# LIBR and the current is any.  
#  
AddSkipOnRepositoryChange("HOLD", "LIBR", "*");
```

Skip an update if the proposed change is HOLD, the target Repository is LIBR and the current Repository is OFFS, LEGL or DEST.

```
#  
# Skip an update if the proposed change is HOLD, the target Repository is  
# LIBR and  
# the current is OFFS, LEGL or DEST.  
#  
AddSkipOnRepositoryChange("HOLD", "LIBR", "*(OFFS|LEGL|DEST)");
```

Skip any update that attempts to move a Volume out of Current Repository DEST.

```
#  
# Skip an update if the proposed change is any, the target Repository is any  
# and the current is DEST.  
#  
AddSkipOnRepositoryChange("*", "*", "DEST");
```

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/engine/sync/addskiponrepositorychange?rev=1566528583>

Last update: **2025/01/21 22:07**

