# Repository Options

### GUID

### Allowable Volume ID's

When left blank, volumes with any allowable characters can be added to this repository. Filters can be added to force all new volumes added to conform to certain criteria.

```
Adding ??????L? will force all new volumes to have 8 characters including an
L in the 7th position.
Adding US* will force all new volumes to start with a US prefix.
```

### Type

### Scratch Mode

### Scratch Priority

### Offsite

### Primary

### No Distribution

### Internal

### Sort Sequence

### Force Simple Management

### No Next Repository

### Allow Deletes

### De-assignment from Container

### Empty Container

### Do not slot if Container

### Don not slot

### Require Tag

### Require Tag Reset

### No re-move

### Dissallow backward next move date changes

### Reset Data Cluster

### Confirm Container Contents

### Move Container Contents

### Late Threshold

### Highwater offset

### Movement Mode

### Next Repository

### Enable Slotting

## Capacity

Capacity

- In Use
- Incoming
- Outgoing
- Minimum Scratch
- Scratch

## Coordinates

Coordinates

- Latitude
- Longitude

From:
https://rtfm.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
**https://rtfm.tapetrack.com/master/repository_options?rev=1500312693**

Last update: **2025/01/21 22:07**