Repository

A Repository represents the general location of a Volume.

Repository-ID

A Repository-ID is a string of up to four alphanumeric characters and is permanently assigned at creation.

Each Repository-ID must be unique within its' Media type.

Description

A Repository object has a description field. This allows a user-friendly description of up to twenty alphanumeric characters to be associated with the Repository-ID.

Dependencies

- Media type (parent)

Options

- allow_deletes
- allow_overlaps
- allowable_volume_ids
- capacity
- confirm_container_contents
- coordinates
- deassign_from_container
- disallow_backward_next_move_date_changes
- do_not_slot_if_container
- do_not_slot
- empty_container
- enable_slotting
- force_simple_management
- guid
- highwater_offset
- internal
- late_threshold
- move_container_contents
- movement_mode
- next_repository

- no_distribution
- no_next_repository
- no_remove
- offsite
- primary
- require_tag_reset
- require_tag
- reset_data_cluster
- retain_moving_slot
- scratch_mode
- scratch_priority
- sort_sequence
- type

Creating a Repository

A Repository Object can be created using:

- Adding and managing a Repository with TapeTrack TapeMaster.

From:
https://rtfm.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/object/repository?rev=1555086669

Last update: **2025/01/21 22:07**