

Repository

A Repository represents the general location of a [Volume](#).

Repository-ID

A Repository-ID is a string of up to four alphanumeric characters and is permanently assigned at creation.

Each Repository-ID must be unique within its' [Media type](#).

Description

A Repository object has a Description field. This allows a user-friendly description of up to twenty alphanumeric characters to be associated with the Repository-ID.

Dependencies

- [Media type](#) (parent)

Options

- [allow_deletes](#)
- [allow_overlaps](#)
- [allowable_volume_ids](#)
- [capacity](#)
- [confirm_container_contents](#)
- [coordinates](#)
- [deassign_from_container](#)
- [disallow_backward_next_move_date_changes](#)
- [do_not_slot_if_container](#)
- [do_not_slot](#)
- [empty_container](#)
- [enable_slotting](#)
- [force_simple_management](#)
- [guid](#)
- [highwater_offset](#)
- [internal](#)
- [late_threshold](#)
- [move_container_contents](#)
- [movement_mode](#)
- [next_repository](#)

- [no_distribution](#)
- [no_next_repository](#)
- [no_remove](#)
- [offsite](#)
- [primary](#)
- [require_tag_reset](#)
- [require_tag](#)
- [reset_data_cluster](#)
- [retain_moving_slot](#)
- [scratch_mode](#)
- [scratch_priority](#)
- [sort_sequence](#)
- [type](#)

Creating a Repository

A Repository Object can be created using:

- [Adding and managing a Repository with TapeTrack TapeMaster.](#)

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/object/repository?rev=1572994129>

Last update: **2025/01/21 22:07**

