

Repository

A Repository represents the general location of a [Volume](#).

Repository-ID

A Repository-ID is a string of up to four alphanumeric characters and is permanently assigned at creation.

Each Repository-ID must be unique within its' [Media type](#).

Description

A Repository object has a Description field. This allows a user-friendly description of up to twenty alphanumeric characters to be associated with the Repository-ID.

Dependencies

- [Media type](#) (parent)

Options

- [allow_deletes](#)
- [allow_overlaps](#)
- [allowable_volume_ids](#)
- [capacity](#)
- [confirm_container_contents](#)
- [coordinates](#)
- [deassign_from_container](#)
- [disallow_backward_next_move_date_changes](#)
- [do_not_slot_if_container](#)
- [do_not_slot](#)
- [empty_container](#)
- [enable_slotting](#)
- [force_simple_management](#)
- [guid](#)
- [highwater_offset](#)
- [internal](#)
- [late_threshold](#)
- [move_container_contents](#)
- [movement_mode](#)
- [next_repository](#)

- [no_distribution](#)
 - [no_next_repository](#)
 - [no_remove](#)
 - [offsite](#)
 - [primary](#)
 - [require_tag_reset](#)
 - [require_tag](#)
 - [reset_data_cluster](#)
 - [retain_moving_slot](#)
 - [scratch_mode](#)
 - [scratch_priority](#)
 - [sort_sequence](#)
 - [type](#)
-
- [Allow Deletes](#) 2019/04/09 01:44 Scott Cunliffe
 - [Allow Overlaps](#) 2019/11/11 23:16 Scott Cunliffe
 - [Allowable Volume-ID's](#) 2019/11/12 01:18 Scott Cunliffe
 - [Capacity](#) 2019/04/18 02:10 Scott Cunliffe
 - [Confirm Container Contents](#) 2019/04/11 02:53 Scott Cunliffe
 - [Coordinates](#) 2019/04/18 02:18 Scott Cunliffe
 - [De-Assign From Container](#) 2019/04/09 02:44 Scott Cunliffe
 - [Disallow Backward Next Move Date Changes](#) 2019/04/11 01:51 Scott Cunliffe
 - [Do Not Slot](#) 2019/04/09 03:46 Scott Cunliffe
 - [Do Not Slot If Container](#) 2019/04/09 03:34 Scott Cunliffe
 - [Empty Container](#) 2019/04/09 03:13 Scott Cunliffe
 - [Enable Slotting](#) 2019/04/18 01:39 Scott Cunliffe
 - [Force Simple Management](#) 2019/04/08 03:48 Scott Cunliffe
 - [GUID](#) 2019/04/18 02:49 Scott Cunliffe
 - [Highwater Offset](#) 2019/04/18 00:23 Scott Cunliffe
 - [Internal](#) 2019/04/08 01:51 Scott Cunliffe
 - [Late Threshold](#) 2019/04/11 04:24 Scott Cunliffe
 - [Move Container Contents](#) 2019/04/11 03:17 Scott Cunliffe
 - [Movement Mode](#) 2019/04/18 00:59 Scott Cunliffe
 - [Next Repository](#) 2019/04/18 01:25 Scott Cunliffe
 - [No Distribution](#) 2019/04/08 01:39 Scott Cunliffe
 - [No Next Repository](#) 2019/11/11 23:15 Scott Cunliffe
 - [No Re-Move](#) 2019/04/11 01:42 Scott Cunliffe
 - [Offsite](#) 2019/04/08 01:24 Scott Cunliffe
 - [Primary](#) 2019/04/08 01:34 Scott Cunliffe
 - [Require Tag](#) 2019/11/11 23:18 Scott Cunliffe
 - [Require Tag Reset](#) 2019/11/11 23:18 Scott Cunliffe
 - [Reset Data Cluster](#) 2019/04/11 02:40 Scott Cunliffe
 - [Retain Moving Slot](#) 2019/11/11 02:36 Scott Cunliffe
 - [Scratch Mode](#) 2019/04/08 00:42 Scott Cunliffe
 - [Scratch Priority](#) 2019/04/08 01:13 Scott Cunliffe
 - [Show Built In Repositories](#) 2019/05/15 02:57 Scott Cunliffe

- [Sort Sequence](#)
- [Type](#)

2019/04/08 03:08 Scott Cunliffe

2019/04/07 23:59 Scott Cunliffe

Creating a Repository

A Repository Object can be created using:

- [Adding and managing a Repository with TapeTrack TapeMaster.](#)

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/object/repository?rev=1572994731>

Last update: **2025/01/21 22:07**

