Repository

A Repository represents the general location of a Volume.

Repository-ID

A Repository-ID is a String of up to four alphanumeric characters and is permanently assigned at creation.

Each Repository-ID must be unique within its' Media type.

The Repository-ID can be viewed in the Repository Properties Identity tab. To open the Repository Properties window, right click on a Repository, in the bottom of the TapeMaster Inventory window, and click `Properties`.

Description

A Repository object has a Description field. This allows a user-friendly description of up to twenty alphanumeric characters to be associated with the Repository-ID.

The Repository Description can be viewed in the Repository Properties Identity tab. To open the Repository Properties window, right click on a Repository, in the bottom of the TapeMaster Inventory window, and click `Properties`.

Dependencies

- Media type (parent)

Options

- Allow Deletes
- Allow Overlaps
- Allowable Volume-ID's
- Capacity
- Confirm Container Contents
- Coordinates
- De-Assign From Container
- Disallow Backward Next Move Date Changes
- Do Not Slot
- Do Not Slot If Container
- Empty Container

- Enable Slotting
- Force Simple Management
- GUID
- Highwater Offset
- Internal
- Late Threshold
- Move Container Contents
- Movement Mode
- Next Repository
- No Distribution
- No Next Repository
- No Re-Move
- Offsite
- Primary
- Require Tag
- Require Tag Reset
- Reset Data Cluster
- Retain Moving Slot
- Scratch Mode
- Scratch Priority
- Show Built In Repositories
- Sort Sequence
- Type

Creating a Repository

A Repository Object can be created using:

- Adding and managing a Repository with TapeTrack TapeMaster.

From:
https://rtfm.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/object/repository?rev=1600912645

Last update: **2025/01/21 22:07**