

# Restoring Replicant Server To Master Server Status

Navigate to TapeTrack Framework Server installation folder (default installation location C:\Program Files\TapeTrack\TapeTrack Framework Server)

[Stop the TapeTrack Framework Service.](#)

Open the file TapeTrack\TapeTrack Framework Server\var\db\DB\_CONFIG in a text editor such as Notepad.

Using the # symbol comment out the lines of code:

```
rep_set_priority 0
repmgr_site replicant-1.tapetrack.com 5010 db_local_site on
repmgr_site master.tapetrack.com 5010 db_bootstrap_helper on
rep_set_config DB_REP_CONF_BULK on
```

to match the following example

```
#rep_set_priority 0
#repmgr_site replicant-1.tapetrack.com 5010 db_local_site on
#repmgr_site master.tapetrack.com 5010 db_bootstrap_helper on
#rep_set_config DB_REP_CONF_BULK on
```

Save the file.

From:  
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:  
[https://rtfm.tapetrack.com/server/replicant\\_to\\_master?rev=1532003787](https://rtfm.tapetrack.com/server/replicant_to_master?rev=1532003787)

Last update: **2025/01/21 22:07**

