2025/12/01 07:44 1/5 Enabling Replication

# **Enabling Replication**

To enable TapeTrack High Availability Replication:

# **Steps On Remote Server**


Install the TapeTrack Framework Server software on your remote machine.

Stop the service on the remote machine.

Delete all database files on the remote machine (all files in the var/db directory EXCEPT the DB CONFIG file).



Do Not delete the DB CONFIG file.



Edit the DB\_CONFIG file and remove the comments (#'s) starting from the line **rep-set-priority 0** to make the machine a Replicant.

```
DB_CONFIG - Notepad
File Edit Format View Help
set verbose DB VERB WAITSFOR
#rep set priority 1
#repmgr site replicant-1.tapetrack.com 5010
#repmgr site master.tapetrack.com 5010 db local site on db group crea
# Optional settings
#
#rep set config DB REP CONF BULK on
#rep set config DB REP CONF AUTOINIT off
#
#
#rep set priority 0
#repmgr site replicant-1.tapetrack.com 5010 db local site on
#repmgr site master.tapetrack.com 5010 db bootstrap helper on
#rep set config DB REP CONF BULK on
```

Edit the Replicant Server and Master Server host names in the DB CONFIG file.

- Replace replicant-1.tapetrack.com 5010 with the IP address of your Replicant Server.
- Replace master.tapetrack.com 5010 with the IP address of your Master Server.



Ensure you use the IP4 address for the Master and Replicant Server as using the domain name can cause issues with the IP6 address replacing the IP4 address, stopping the Master and Replicant communication.

https://rtfm.tapetrack.com/ Printed on 2025/12/01 07:44

2025/12/01 07:44 3/5 Enabling Replication

```
##rep_set_config DB_REP_CONF_BULK on
#rep_set_priority 0
repmgr_site RRR.RRR.RRR.RRR.SO10 db_local_site on
repmgr_site MMM.MMM.MMM 5010 db_bootstrap_helper on
rep_set_config DB_REP_CONF_BULK on
```



Ensure that the replication TCP/IP ports specified in the DB\_CONFIG file are open for inbound connections.

Start the TapeTrack service on the remote machine.

### **Steps On Master Server**

Stop the TapeTrack service on the master TapeTrack server.



Do Not delete any files on the master server

Edit the DB\_CONFIG file and remove the comments (#'s) starting from the line **rep-set-priority 1** to make the machine a master server.

```
DB_CONFIG-Notepad
File Edit Format View Help
set_verbose DB_VERB_WAITSFOR

#
#rep_set_priority 1
#repmgr_site replicant-1.tapetrack.com 5010
#repmgr_site master.tapetrack.com 5010 db_local_site on db_group_crea
#
# Optional settings
#
#rep_set_config DB_REP_CONF_BULK on
#rep_set_config DB_REP_CONF_AUTOINIT off
#
#
#rep_set_priority 0
#repmgr_site replicant-1.tapetrack.com 5010 db_local_site on
#repmgr_site master.tapetrack.com 5010 db_bootstrap_helper on
#rep_set_config DB_REP_CONF_BULK on
```

Edit the DB\_CONFIG file to define the local and remote server. Edit the replication local (master server) and remote (replicant server) host names in the DB\_CONFIG file.

- Replace replicant-1.tapetrack.com 5010 with the domain name (or IP address) of your replicant server.
- Replace master.tapetrack.com 5010 with the domain name (or IP address) of your master server.

```
## "PB_CONFIG - Notepad
File Edit Format View Help
set_verbose DB_VERB_WAITSFOR
#
rep_set_priority 1
repmgr_site RRR.RRR.RRR.RRR 5010
repmgr_site MMM.MMM.MMM 5010 db_local_site on db_group_creator or
#
# Optional settings
#
#rep_set_config DB_REP_CONF_BULK on
#rep_set_config DB_REP_CONF_AUTOINIT off
#
#
# "rep_set_priority 0
# "repmgr_site replicant-1.tapetrack.com 5010 db_local_site on
# "rep_set_config DB_REP_CONF_BULK on
# "repmgr_site master.tapetrack.com 5010 db_local_site on
# "rep_set_config DB_REP_CONF_BULK on
```

https://rtfm.tapetrack.com/ Printed on 2025/12/01 07:44

2025/12/01 07:44 5/5 Enabling Replication



Ensure that the replication TCP/IP ports are open for inbound/outbound connections.

Start the master TapeTrack server.

## **Confirming Functionality Of Primary And Replicant Servers**

Open \$DB\_Msg.txt file (in the var/db directory) on both the primary and replicant server to ensure that replication is functional.



Ensure that all firewall ports are open to allow the replication traffic to pass between the replicants.



The replication communications are not encrypted so if replication is enabled you should ensure that all machines that are replicated are in a trusted network or connected via a secure VPN connection.

Server replication troubleshooting

#### See Also

Restoring replicant server to master server status

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/server/replication?rev=1578440677

Last update: 2025/01/21 22:07

