# **Decommissioning Server Replication**

## **DB** Config File

On the server that your master Framework Server is installed, navigate in Windows File Explorer to the TapeTrack Installation folder (default = C:\Program Files\TapeTrack\TapeTrack Framework Server\var\db) and open the file DB\_CONFIG with a text editor such as Notepad.

×						
File	Home Share View				,	~ 🕐
$\leftarrow \rightarrow \checkmark \uparrow$ – « Program Files » TapeTrack » TapeTrack Framework Server » var » db v Ö $\land$ Server » var » db						
	Name	Date modified	Туре		Size	^
>42	DB_CONFIG	6/15/2013 2:45 AM	File			
> 📙	TMSS10.attribute-history	2/11/2022 11:33 AM	ATTRIBUTE-HISTORY File			
>	TMSS10.attribute-history.dump	11/6/2021 11:12 AM	DUMP File			
	TMSS10.attribute-history.save	9/2/2021 9:45 AM	SAVE File			
	TMSS10.attributes	2/11/2022 11:33 AM	ATTRIBUTES File			
Y 💻 1	TMSS10.attributes.dump	11/6/2021 11:12 AM	DUMP File			
> 🧊	TMSS10.attributes.save	9/2/2021 9:45 AM	SAVE File			
>	TMSS10.attributetype	2/11/2022 10:41 AM	ATTRIBUTETYPE File			
> 🔮	TMSS10.attributetype.dump	11/6/2021 11:12 AM	DUMP File			
51	TMSS10.attributetype.save	9/2/2021 9:45 AM	SAVE File			
	TMSS10.barcode	2/3/2022 1:03 PM	BARCODE File			
	TMSS10.barcode.dump	11/6/2021 11:12 AM	DUMP File			
> 🔤	TMSS10.barcode.save	9/2/2021 9:45 AM	SAVE File			
> 📑	TMSS10.catalog	9/2/2021 11:29 AM	CATALOG File			
> 🏥	TMSS10.catalog.dump	11/6/2021 11:12 AM	DUMP File			
> _	TMSS10.catalog.save	9/2/2021 9:45 AM	SAVE File			
	TMSS10.catalog-extent	9/2/2021 11:29 AM	CATALOG-EXTENT File			
2 💆 ľ	TMSS10.catalog-extent.dump	11/6/2021 11:12 AM	DUMP File			4
~	<					>
222 items	2 items selected 128 KB				8	E 💌 🛛

## **Edit Config File**

Scroll to the bottom of the config file until you see the replication code section

```
rep_set_priority 1
repmgr_site replicant-1.tapetrack.com 5010
repmgr_site master.tapetrack.com 5010 db_local_site on db_group_creator on
```

Add a hash tag to the start of the lines of code to convert them to comments so they will be skipped when TapeTrack loads the config file.

```
#rep_set_priority 1
#repmgr_site replicant-1.tapetrack.com 5010
#repmgr_site master.tapetrack.com 5010 db_local_site on db_group_creator on
```

Last update: 2025/01/21 22:07 server:replication\_decomission https://rtfm.tapetrack.com/server/replication\_decomission?rev=1644889382





Depending on your system setup you may need to add write permissions to allow your user-ID to save the config file.

Save the file, ensuring that it saves as DB\_CONFIG.cfg and not .txt

#### **Stop The Server**

Follow instructions at Stop the Server.

S	TapeTrack Server Helper		×
Ξ	Service		
	Name	TMSS10SVC	
	Status	Running	
	Process ID	15124	
	Binary	C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe	
Ξ	Options		
	Home Directory		
	Port	5000	
	Syslogd Server		
	Enable Replication	True	
	Log File Name Type	0	
le le	<u>S</u> ave Service Setti	ngs	
-			
C	ntrol Service	Update Software Edit/View Files	
1.000			

The embedded database used by TapeTrack uses transactional protection. This means that as updates are applied to the underlying database, they are first written to a log file.

If you plan to not make use of replication again disabling the replication subsystem will allow the database to automatically remove any log files that are no longer active and save on disk space. This can be accomplished easily by using the Framework Server Helper (recommended method) or by

direct registry edit (advanced method).

Instructions for disabling the replication subsystem can be viewed at Disable Replication

3/4

S	TapeTrack Server Helper		×		
	Service	THECLOCHE			
	Status	Stopped			
	Binary	C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe			
Ξ	Options				
	Home Directory				
	Port	5000			
	Syslogd Server				
	Enable Replication	True			
	Log File Name Type	0			
k	<u>S</u> ave Service Setting	IS and the second se			
Co	ontrol Service	Update Software Edit/View Files			
(	Stop	Start Download and Update DB_CONFIG \$DB_Err			

#### **Start The Server**

Follow instructions at Start the Server.

S	TapeTrack	Server Helper		×
8	Service Name Status	5	TMSS10SVC Stopped	
Ξ	Options Home Dire	ectory		
	Port Syslogd S	erver	5000	
	Enable Re Log File N	eplication Jame Type	False	
k		Save Service Settin	ings	
Co	ontrol Servi	ice	Update Software Edit/View Files	
_		Stop	Start Download and Update DB_CONFIG	\$DB_Err

You can now login to the TapeTrack Desktop Software as usual.

### **Stop Replicant Database**

Navigate to the location of your Replicant Server installation and Stop the Server.

From: https://rtfm.tapetrack.com/ - **TapeTrack Documentation** 

Permanent link: https://rtfm.tapetrack.com/server/replication\_decomission?rev=1644889382



Last update: 2025/01/21 22:07