


Decommissioning Server Replication

DB Config File

On the server that your master Framework Server is installed, navigate in Windows File Explorer to the TapeTrack Installation folder (default = C:\Program Files\TapeTrack\TapeTrack Framework Server\var\db) and open the file DB_CONFIG with a text editor such as Notepad.




Edit Config File

Scroll to the bottom of the config file until you see the replication code section


```
rep_set_priority 1
repmgr_site replicant-1.tapetrack.com 5010
repmgr_site master.tapetrack.com 5010 db_local_site on db_group_creator on
```

Add a hash tag to the start of the lines of code to convert them to comments so they will be skipped when TapeTrack loads the config file.

```
#rep_set_priority 1
#repmgr_site replicant-1.tapetrack.com 5010
#repmgr_site master.tapetrack.com 5010 db_local_site on db_group_creator on
```




```
File Edit Format View Help
#
# Set the Cache Size
#
set_cachesize 0 50000000 2
#
# Set lockers and locks
#
set_lk_max_lockers 100000
set_lk_max_locks 100000
set_lk_max_objects 100000
#
# Set the log size of 1 MB. Comment out for default of 10 MB
#
#set_lg_max 1048576
#
# Remove the Log AutoRemove Comment if you want to auto delete logs
#
set_flags DB LOG AUTOREMOVE
```

 Depending on your system setup you may need to add write permissions to allow your user-ID to save the config file.

Save the file, ensuring that it saves as DB_CONFIG.cfg and not .txt

Stop The Server

Follow instructions at [Stop the Server](#).



Service	
Name	TMSS10SVC
Status	Running
Process ID	15124
Binary	C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe

Options	
Home Directory	
Port	5000
Syslogd Server	
Enable Replication	True
Log File Name Type	0


Buttons: Save Service Settings, Control Service (Stop, Start), Update Software (Download and Update), Edit/View Files (DB_CONFIG, \$DB_Err)

The embedded database used by TapeTrack uses transactional protection. This means that as updates are applied to the underlying database, they are first written to a log file.

If you plan to not make use of replication again disabling the replication subsystem will allow the database to automatically remove any log files that are no longer active and save on disk space. This can be accomplished easily by using the Framework Server Helper (recommended method) or by


direct registry edit (advanced method).

Instructions for disabling the replication subsystem can be viewed at [Disable Replication](#)



Start The Server

Follow instructions at [Start the Server](#).



You can now login to the TapeTrack Desktop Software as usual.

Stop Replicant Database

Navigate to the location of your Replicant Server installation and [Stop the Server](#).

[replication](#), [server](#), [registry](#), [technote](#)

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/server/replication_decomission?rev=1644894223

Last update: **2025/01/21 22:07**

