

Synchronization Prerequisites And Considerations

Synchronization Prerequisite

To be able to synchronize you will need the following components and information:

1. The TapeTrack Synchronization Suite software fully installed.
2. The address and port of your TapeTrack Server.
3. The User-ID and password of your TapeTrack Server.
4. The TapeTrack Customer-ID and Media-ID for the tapes being synchronized.
5. The TapeTrack Repository-IDs for each location that a tape volume may be moved to.
6. The ability to extract data from your backup or tape management software using either an ODBC connection or command line interface.
7. Access to schedule a task under Windows Task Scheduler or cron(8).

CPU and bandwidth considerations

The TapeTrack Synchronization Suite programs are written in C and are optimized to use minimal bandwidth and CPU.

To calculate the potential bandwidth used during a synchronization, the program will download a cache of volume information with each volume record consisting of approximately 300 bytes. If the volume also has a description, an additional 256 bytes may be downloaded.

This means that if you have a library of 10,000 tape volumes, each of which has a description the cache will be: $(10,000 \times 300 \text{ bytes}) + (10,000 \times 256 \text{ bytes}) = 5.5 \text{ megabytes}$.

The 5.5 megabytes is then compressed using level 9 gzip(3) compression which usually compresses down to approximately 1 megabyte.

Then, if 100 tapes are updated, this would consume $(100 \times 300 \text{ bytes} + 100 \times 256 \text{ bytes}) = 55\text{KB}$ of uploaded data. This data is usually compressed at a ratio of 2:1, which means that the total upload bandwidth is around 28KB.

From:
<https://rtfm.tapetrack.com/> - TapeTrack Documentation

Permanent link:
<https://rtfm.tapetrack.com/sync/prerequisites?rev=1622598287>

Last update: **2025/01/21 22:07**

