TapeTrack Documentation - https://rtfm.tapetrack.com/

# **Adjusting Slot Allocation**

From time to time you may need to adjust a Customers Slot allocation based on increased or decreased Volume numbers.

## **Increasing Slot Allocation**

Slotting allocation can be increased by either adding extra zones to the Repository, or by increasing the Slot allocation within the currently assigned Zones.

See Maintaining A Zone to add or increase Zone allocation.

## **Decreasing Slot Allocation**

### **Removing Empty Slots**

Decreasing Slot allocation for a Customer can be as simple as reducing the Slots allocated through the Slot **Edit Range Information** window, as long as the Slots being removed are sequential, unoccupied and from the end of the last Zone allocated.

Removing Slot allocation using this method must be from the last allocated Zone (if multiple Zones are assigned) from the high end of the Zone. The reason for this is if there are three Zones allocated, each with 100 Slots, TapeTrack interprets these as one continual Slot arrangement, 1 to 100 in Zone 1, 101 to 200 in Zone 2 and 201 to 300 in Zone 3. Reducing the Slot allocation from 300 to 250 by removing the last 50 Slots from Zone 3 keeps all lower Slotted tapes in the same number Slot. So a tape in Slot 248 would still in the same place (Zone 3, 48th slot). If you were to remove the 50 Slots in Zone 2, Zone 1 would still be Slots 1 to 100, Zone 2 would now be Slots 101 to 150 and Zone 3 would be 151 to 250, essentially putting Slot 248 now in the 98th Slot in Zone 3. This would put all Volumes in Zone 3 out 50 Slots in allocation vs physical location.

#### **Removing Occupied Slots**

If the Slots to be removed from allocation are currently occupied, completely or partially, the Volumes will need to be reslotted before this can be accomplished.



You must have enough empty Slots under the highwater mark to accommodate any Volumes currently slotted above the mark.

To remove these Volumes from the occupied Slots:

• Right click the required Repository and select Properties, or double click the Repository , and click on the Options tab.

Last update: 2025/01/21 technote:adjusting\_slot\_allocation https://rtfm.tapetrack.com/technote/adjusting\_slot\_allocation?rev=1638837378

Image: TapeTrack TapeMaster™ (GazillaByte)     -     -     ×       File     Administration     Fourierity     Taple     View     Hale						
Customer Filter						
GazillaByte - Production US00 - United State: US01 - New York US02 - Los Angel	<ul> <li>Inventory O DR Strategies ( Data Clusters O Simple Management Uploaded Files O Consignments</li> <li>Volumes</li> </ul>					
		Contraction	Transfer	<b>Flam</b>	Next Maxie	Description
LTO - LTO Car	Entertext I	Enter text here	Enter text		Enter text here	Sector text here
🖭 🧊 US03 - North Caro		Enter text here	Y Entertext Y	Cn Y	Enter text here	Y Entertext nere Y
, i i i i i i i i i i i i i i i i i i i	00000016	Gem Irac		Cn Cn		
	00000116	Red 1 [10 1]		C0		
	00000316	Red 1 [8 6]		CNO		Friday Backup
	00000416	Red 1 [9.5]		CNO		Friday Backup
	00000516	Red 1 [3.2]		CNO		Friday Backup
	000006L6	Red 1 [3.3]		CNO		Monthly January
	00000716	Red 1 [2.5]		CO		
	E 000008L6	GemTrac		Cn		
	C00009L6	Library		CnN		Friday Backup
	E 000010L6	🏽 Red 1 [2.4]		CO		
	E 000011L6	🐞 Red 1 [3.7]		CO		
	🔜 000012L6	🎬 Red 1 [3.4]		CO		
	E 000013L6	Library		Cn		
	🛲 000014L6	🎬 Red 1 [3.5]		CO		
	💻 000015L6	GemTrac		Cn		
	E 000016L6	GemTrac		Cn		
	💻 000017L6	GemTrac	Library	CMn		:
	E 000018L6	GemTrac	Library	CMn		:
	E 000019L6	GemTrac	Library	CMn		:
	a 000020L6	GemTrac	Library	CMn		
	Total Items 263	GomTrac		<u></u>	Total Selected 1	First Selection 16
	Demotioning 200				Total Sciected	Inst Selection 10
	Repositories					388
			Ro			
< >	GemTrac	Library	Offsite Vault			
			0	Connectio	on 127.0.0.1 uses AES 256 b	it encryption 🕞 Tape

• Set Highwater Offset to the number you wish to lower Slot allocation by. For example if you currently have 3000 Slots allocated and wish to reduce the allocation to 1000 Slots set the highwater offset to 2000 (3000 - 2000).

×

- Run the slotting program TMSS10SlotAllocation to re-slot any Volumes above the highwater mark.
- Decrease the slot allocation.

×

• Adjust the **Highwater Offset** back to zero to enable use of all allocated Slots.

×

Permanent link: https://rtfm.tapetrack.com/technote/adjusting\_slot\_allocation?rev=1638837378



Adjusting Slot Allocation

Last update: 2025/01/21 22:07