# **Disabling Journal And Volume History Entries**

When Volumes are added, moved or altered, by default TapeTrack adds entries to the Journal and History databases.

If you wish to change this behavior you can pass arguments to the TapeTrack Server to completely disable this logging, or selectively disable this logging for specific Customers.

We strongly recommend against ever using this feature unless you:

do not use the Journall facilities and want to save overhead and disk space, or



 have a very specific need to perform operations without Volume History being created. We strongly recommend that you never do this.

When this feature is used a record will be written to the Journal to record that it has been used.

## **Disabling Journal Entries**

#### Stop the Framework Server.

Backup Registry before making any alterations. Do not edit the registry unless you are competent to do so.

Disabling the journal entries is achieved by adding an attribute to the registry entry for the Framework Sever. Once you have a current backup of the registry, navigate to Computer\HKEY\_LOCAL\_MACHINE\SYSTEM\ControlSet001\Services\TMSS10SVC in Registry Editor.

ile Edit View Favorites Help			
omputer\HKEY_LOCAL_MACHINE\SY	STEM\ControlSet001\Services\TMSS10SV0	C	
Computer HKEY_CLASSES_ROOT HKEY_CURRENT_USER HKEY_LOCAL_MACHINE SYSTEM ControlSet001 Services TMSS105VC	Name  DelayedAutostart  DependOnService  Description  DisplayName  ErrorControl  DisplayName  Start  Start	Type REG_SZ REG_DWORD REG_MULTI_SZ REG_SZ REG_SZ REG_EXPAND_SZ REG_SZ REG_DWORD	Data (value not set) 0x0000001 (1) Tcpip Provides Tape Management functionality for TapeTrack enabled applications. TapeTrack Media Management Framework Server 0x0000003 (3) "C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" LocalSystem 0x00000002 (2)
	and Start	REG_DWORD REG_DWORD	0x0000002 (2) 0x00000010 (16)

Double click on the Image Path to open up the Edit String window.

At the end of the Value data string, add the string required to disable the journal entries for the required Customer-ID's based on the following examples and click OK to commit the changes.

Disable journal entries for all Customers:

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J
#DiSaBlE

If you have replication disabled on your server, the registry entry will have a -X option, if this is the case simply add the -J option after that.

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -X
-J #DiSaBlE
```

Disable journal entries for all Customer US01:

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J
US01

Disable journal entries for all Customers US01 and US03:

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J
"\*(US01|US03)"

Start the Framework Server.

### **Enabling Journal Entries**

TapeTrack will no longer add journal entries for the Customers added to the registry entry. To restore the database back to adding journal entries: Stop the Framework Server.

Open the registry and edit the ImagePath string entry to remove the -J value entry and click OK to commit the change.

Start the Framework Server.

### **Disabling History Entries**

Stop the Framework Server.



Backup Registry before making any alterations. Do not edit the registry unless you are competent to do so.

Disabling the history entries is achieved by adding an attribute to the registry entry for the Framework Sever. Once you have a current backup of the registry, navigate to Computer\HKEY\_LOCAL\_MACHINE\SYSTEM\ControlSet001\Services\TMSS10SVC in Registry Editor.

File Edit View Favorites Help Computer\HKEY_LOCAL_MACHINE\SYSTE	M\ControlSet001\Services\TMSS10SVC		
Computer HKEY_CLASSES_ROOT HKEY_CURRENT_USER HKEY_LOCAL_MACHINE SYSTEM ControlSet001 Services	Name  (Default)  DelayedAutostart  DependOnService  Description  DisplayName  ErrorControl  ImagePath  ObjectName  Start  Type	Type REG_SZ REG_DWORD REG_MULTI_SZ REG_SZ REG_SZ REG_DWORD REG_EXPAND_SZ REG_SZ REG_DWORD REG_DWORD	Data (value not set) 0x00000001 (1) Tcpip Provides Tape Management functionality for TapeTrack enabled applications. TapeTrack Media Management Framework Server 0x00000003 (3) "C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" LocalSystem 0x0000002 (2) 0x00000010 (16)

Double click on the Image Path to open up the Edit String window.

At the end of the Value data string, add the string required to disable the journal entries for the required Customer-ID's based on the following examples and click OK to commit the changes.

Disable history entries for all Customers:

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -H
#DiSaBlE

If you have replication disabled on your server, the registry entry will have a -X option, if this is the case simply add the -H option after that.

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -X
-H #DiSaBlE

Disable history entries for all Customer US01:

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -H US01

Disable history entries for all Customers US01 and US03:

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -H
"*(US01|US03)"
```

Start the Framework Server.

#### **Enabling History Entries**

TapeTrack will no longer add history entries for the Customers added to the registry entry. To restore the database back to adding history entries: Stop the Framework Server.

Open the registry and edit the ImagePath string entry to remove the -H value entry and click OK to commit the change, remembering to leave the -X if it was previously present.

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe"

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -X

Start the Framework Server.

### **Disabling Journal And History Entries**

If you want to disable both journal and history entries, add the -J and -H the registry string ImagePath consecutively.

Disable journal entries for all Customers:

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J
#DiSaBlE -H #DiSaBlE

If you have replication disabled on your server, the registry entry will have a -X option, if this is the case simply add the -J option after that.

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -X
-J #DiSaBlE -H #DiSaBlE
```

Disable journal entries for all Customer US01:

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J
US01 -H US01
```

Disable journal entries for all Customers US01 and US03:

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J
"*(US01|US03)" -H "*(US01|US03)"
```

Start the Framework Server.

#### **Enable Journal And History Entries**

TapeTrack will no longer add journal or history entries for the Customers added to the registry entry. To restore the database back to adding journal entries:

Stop the Framework Server.

Open the registry and edit the ImagePath string entry to remove the -J value entry and click OK to commit the change, remembering to leave the -X if it was previously present.

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe"

"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -X

#### Start the Framework Server.

#### technote, registry, server, new feature

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link: https://rtfm.tapetrack.com/technote/journal\_history?rev=1737423075



Last update: 2025/01/21 22:07