

Dealing With Barcodes Longer Than 10 Characters In Length

TapeTrack has a Volume-ID limit of 10 characters in length. Any volumes with an ID longer than 10 characters must be modified to fit within this criteria.

There are several ways in which can be achieved, such as truncation, translation or hashing.

Truncation

Truncating a barcode, or volume-ID, involves trimming off the start or end down to 10 or fewer characters.

Truncating a barcode can be achieved by several different methods.

Truncation Via The Scan In Window

Barcodes can be truncated via the TapeTrack Scan window in TapeMaster, Lite and Checkpoint.



This method only truncates volume-ID's through the scan window

[Information on truncating a barcode via the scan window.](#)

Truncation Via Media Properties In TapeMaster

Truncation of a barcode by removing the suffix (eg removing L6 from 1234567890L6) can be achieved by setting the Remove Suffix option in the media properties via TapeMaster.



This method will truncate all matching volume-ID's regardless of length and will only act on the suffix

Truncating a barcode via the [media properties](#) tab. Adding L6 in the Remove Suffix field will remove L6 from any matching volume-ID (eg removing L6 from 1234567890L6 to input as 1234567890 or 123456L6 as 123456) regardless of barcode length.

Adding L* will remove any 2 digit suffix from the volume-ID that starts with L (eg 123456L6 will truncate to 123456, 1000000001L3 will truncate to 1000000001)

Translation

Translating a barcode, or volume-ID, involves swapping a recognisable pattern for an alternate value within the 10 character limit via translation statements in a ttidef file.



This method works with command line programs, such as [TMSS10Sync](#), via ttidef file statements as well as through configuration files in TapeMaster, Lite and Checkpoint.

Using a translation statement **AddTranslation(VOLUME, "A6???????????", "^~^~^~^~^~^~^~^~^");** in the ttidef file, any 12 character volume-ID starting with A6, such as A61234567890, will drop the first two characters and keep the next 10, inputting as 1234567890.

Hashing

Hashing a barcode, or volume-ID, involves replacing the barcode with its 8 character hashed value, preceded by the value #- to allow identification that the volume-ID has been hashed. It is a good practice to put the true, or un-hashed, barcode in the attribute field to enable a human readable value as well as the hashed volume-ID.



Barcodes can be hashed via ttidef files for command line programs as well as through configuration files in TapeMaster, Lite and Checkpoint.

Using a translation statement **AddTranslation(VOLUME, "????????????*?", "#");** in the ttidef file, any 11 character or longer volume-ID will be hashed, so 111111222222 would be hashed to X-2E8CA12F

Using the translation code block below in the configuration files will achieve the same result as the translation statement in the ttidef file above.

```
barcodes=
{
  translations=
  (
    { filter="????????????*?"; value="#" ; }
  );
};
```



Hashing barcodes that have spaces in the middle, such as **Monday 1**, is the simplest method (spaces are not permitted in volume-ID's) for translation to an acceptable value.

The code for handling spaces is **AddTranslation(VOLUME, "*? ?*", "#");** for the ttidef file and **{ filter="*? ?*"; value="#" ; }** for the configuration files.</note>

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

https://rtfm.tapetrack.com/technote/long_barcodes?rev=1541024585

Last update: **2025/01/21 22:07**

