

Restricting Which Volume-ID's Can Be Moved To A Repository.

TapeTrack allows the restriction of what [Volumes](#) can be moved to a Repository based on a pattern specified in the Repository properties.

Setting Volume-ID Restrictions

Open the required [Repository's](#) properties and navigate to the Options tab.

Click in the field to the right of Allowable Volume-ID's and enter allowable [Volumes](#) string pattern.



Restricting [Volume-ID](#) patterns can be enforced using [TapeTrack string filters](#).


[Character filters](#) may be used alone or in combination to achieve the restricted [Volume-ID pattern](#) required.

Example Patterns

Volume-ID required	Filter Pattern	Example Volume-ID
Only Volumes ending in L5	*L5	100001L5
Any Volumes except those ending in L5	!*L5	100002L6
Volumes ending in L5 or starting with X-	*(L5 X-*)	X-2E8CA12F

Any attempt to move a [Volume](#) with a non compliant [Volume-ID](#) will cause an error and the move will be aborted.

Failed Operations ✕

Error	Item	Time
Enter text here <input type="text"/>	Enter text here <input type="text"/>	Enter text here <input type="text"/>
 Disallowed Volume Serial. (see Media or Repository options)	000001L6	2018-06-21 12:39:06

Display results that were OK

OK

[technote](#), [tapemaster](#)

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/technote/restricting_volumeid_by_repository

Last update: **2025/01/21 22:07**

