


# Restricting Which Volume-ID's Can Be Moved To A Repository.

TapeTrack allows the restriction of what volumes can be moved to a repository based on a pattern specified in the Repository properties.

## Setting Volume-ID Restrictions

Open the required repository's properties and navigate to the Options tab.

Click in the field to the right of Allowable Volume-ID's and enter allowable volumes string pattern.



Restricting volume-ID patterns can be enforced using [TapeTrack string filters](#).

Character filters may be used alone or in combination to achieve the restricted volume-ID pattern required.

Any attempt to move a volume with a volume-ID will cause an error and the move will be aborted.

**Failed Operations** [Close]

Error	Item	Time
Enter text here	Enter text here	Enter text here
Disallowed Volume Serial. (see Media or Repository options)	000001L6	2018-06-21 12:39:06

Total Items: 1

Display results that were OK

OK

## Example Patterns

Volume ID required	Filter Pattern	Example Volume-ID
Only volumes ending in L5	*L5	100001L5
Anything except volumes ending in L5	!*L5	100002L6
Volumes ending in L5 or starting with X-	*(L5 X-*)	X-2E8CA12F

From: <https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link: [https://rtfm.tapetrack.com/technote/restricting\\_volumeid\\_by\\_repository?rev=1529548881](https://rtfm.tapetrack.com/technote/restricting_volumeid_by_repository?rev=1529548881)

Last update: **2025/01/21 22:07**

