

Restricting Which Volume-ID's Can Be Moved To A Repository.

TapeTrack allows the restriction of what volumes can be moved to a repository based on a pattern specified in the Repository properties.

Setting Volume-ID Restrictions

Open the required repository's properties and navigate to the Options tab.

Click in the field to the right of Allowable Volume-ID's and enter allowable volumes string pattern.



Restricting volume-ID patterns can be enforced using [TapeTrack string filters](#).


Character filters may be used alone or in combination to achieve the restricted volume-ID pattern required.

Example Patterns

| Volume ID required | Filter Pattern | Example Volume-ID |
|------------------------------------------|----------------|-------------------|
| Only volumes ending in L5 | *L5 | 100001L5 |
| Anything except volumes ending in L5 | !*L5 | 100002L6 |
| Volumes ending in L5 or starting with X- | *(L5 X-*) | X-2E8CA12F |

Any attempt to move a volume with a volume-ID will cause an error and the move will be aborted.

Failed Operations

| Error | Item | Time |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------------------|
| Enter text here | Enter text here | Enter text here |
|  Disallowed Volume Serial. (see Media or Repository options) | 000001L6 | 2018-06-21 12:39:06 |

Total Items 1

Display results that were OK

OK

From: <https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link: https://rtfm.tapetrack.com/technote/restricting_volumeid_by_repository?rev=1529548932

Last update: **2025/01/21 22:07**

