

# Framework Server Command Line Arguments

The following command line arguments can be passed to the Framework Server executable:

| Argument | Type           | Notes  |
|----------|----------------|--|
| -D       | bool           | Records a dump file if the server stops unexpectedly (Linux only)                |
| -f       | bool           | Run the program in foreground mode (Windows only)                                |
| -g       | string         | Location of the file GeoIP.dat, loads country code against active users          |
| -h       | string         | Path to the directory containing the TapeTrack database                          |
| -H       | string         | Disables Volume history entries  |
| -l       | Integer        | Log file format (0=append, 1=truncate, 2=timestamp, 3=stdout/stderr)             |
| -j       | string         | Disable the journal file entries   |
| -L       | bool           | Reload the database  |
| -p       | Integer/string | Port that TapeTrack will listen on. If string, the services file will be checked |
| -S       | string         | Syslogd host in format host:port (default localhost:514)                         |
| -r       | bool           | Allow a one time login to the 'tapemaster' User-ID with a blank password         |
| -X       | bool           | Disable the replication sub-system   |
| -V       | bool           | Print version and exit   |
| -?       | bool           | Show help text   |

## Example

To check what version of the Framework Server you have installed.

```
C:\>TMSS10Server -V
```

```
TapeTrack FrameWork Server. Compiled Jun 15 2020 @ 16:31:16
```

[technote](#), [server](#)

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

[https://rtfm.tapetrack.com/technote/server\\_arguments?rev=1739511215](https://rtfm.tapetrack.com/technote/server_arguments?rev=1739511215)

Last update: **2025/02/14 05:33**

