

# Setting Environmental Variables

The default behaviour of TapeTrack programs can be changed by setting environmental variables.

These variables can be set using the following methods.

## Windows Command Line

```
set VARIABLE=VALUE
```

Where VARIABLE is the variable name, and VALUE is the variable value.

## Linux Shell

To set an environmental variable in the Linux operating system, use the export command.

```
export VARIABLE=VALUE
```

Where VARIABLE is the variable name, and VALUE is the variable value.

## TapeTrack Config File

The TapeTrack Config File that is loaded when each Desktop and Command Line Program is initiated can also be used to set environmental variables.

```
variables = {  
    TMSSLEVELNAMES = "A,B,C";  
    TMSSNOLEVELSLOT = "1";  
};
```

Last update: 2025/01/21 22:07 technote:setting\_environmental\_variables [https://rtfm.tapetrack.com/technote/setting\\_environmental\\_variables?rev=1530306118](https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1530306118)

---

From:  
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:  
[https://rtfm.tapetrack.com/technote/setting\\_environmental\\_variables?rev=1530306118](https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1530306118)



Last update: **2025/01/21 22:07**