Setting Environmental Variables

The default behaviour of TapeTrack programs can be changed by setting environmental variables.

These variables can be set using the following methods.

Windows Command Line

```
set VARIABLE=VALUE
```

Where VARIABLE is the variable name, and VALUE is the variable value.

Linux Shell

To set an environmental variable in the Linux operating system, use the export command.

```
export VARIABLE=VALUE
```

Where VARIABLE is the variable name, and VALUE is the variable value.

You can also prepend the variable to the command.

```
TMSSREPORTFORMAT=CSV TMSS10Inventory
```

TapeTrack Config File

The TapeTrack Config File that is loaded when each Desktop and Command Line Program is initiated, it can also be used to set environmental variables.

```
variables = {
   TMSSLEVELNAMES = "A,B,C";
   TMSSNOLEVELSLOT = "1";
};
```

update: 2025/01/21 technote:setting_environmental_variables https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1549905670

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=154990567

Last update: 2025/01/21 22:07



https://rtfm.tapetrack.com/ Printed on 2025/10/16 12:41